

## LEED DATA SHEET

DATE:	
PROJECT NAME:	
PROJECT LOCATION:	
NAME OF PRODUCT:	POWERply Endure 300FR
DESCRIPTION:	Granule surfaced SBS/RET/TPU modified bitumen membrane with a nonwicking polyester & fiberlass reinforcing fabric, GranuLock surface treatment, and Roof-ID RFID chips.
PRODUCT/MATERIAL COST: \$	

### SOLAR REFLECTIVITY INDEX (SRI)

PAVING & SLOPED ROOF >2:12 MUST BE AT LEAST 29:	N/A
LOW SLOPED ROOF MATERIALS MUST BE AT LEAST 78:	24

### RECYCLED CONTENT

PRE-CONSUMER:	0	%
POST CONSUMER:	0	%

### REGIONAL QUALIFICATIONS FOR PRODUCT/MATERIALS:

		DISTANCE FROM PROJECT:		MILES
LOCATION OF PROCESS:		DISTANCE FROM PROJECT:		MILES
LOCATION OF MANUFACTURE:	Cleveland, OH	DISTANCE FROM PROJECT:		MILES

### LOW EMITTING MATERIALS:

COATING VOC <small>(GRAMS/L)</small>	SEALANT VOC <small>(GRAMS/L)</small>	ADHESIVE VOC <small>(GRAMS/L)</small>	USE OF MATERIAL	

### RAPIDLY RENEWABLE MATERIAL:

PERCENT RENEWABLE:	0	%
COST:	\$	

PREPARED BY:	
--------------	--

*\*Extraction/Process/Manufacture is defined as the assembly of a final product not including on-site assembly or installation.  
 \*\*Due to several sources of raw materials for this product, specifying the origin of the component materials may not be possible.*