

# Tremlite Polyfoil

## Aluminum Seam Sealing Tape For Metal Surfaces

### FEATURES

Superior Adhesion  
Easy, Fast Application  
Modified Butyl Rubber  
Aluminum Foil Surface

### BENEFITS

- Immediate water tight bond
- Reduces Labor Cost
- Stays Flexible
- Excellent UV Resistance

### DESCRIPTION

Tremlite Polyfoil is a 2 mil finish aluminum foil tape laminated to a 33 mil gray elastomeric modified butyl rubber adhesive.

### BASIC USES

Tremlite Polyfoil is used for metal roof overlaps, and is coated with One Coat Aluminum. Tremlite Polyfoil can also be used as a finished product because of its excellent UV resistance. Tremlite Polyfoil provides an instant water tight bond on most metal surfaces. It will conform to surface variations and irregular areas.

### PACKAGING

12 rolls / case

### COLOR

Aluminum foil tape with gray adhesive.

### STORAGE LIFE

2 years in original container under warehouse storage conditions.

### APPLICATION

**Preparation:** Surfaces must be sound, clean and dry free of dirt, oil, debris, dust and other contaminants. Rust and loose paint must be removed by wire brush, scraping, sanding, or power washing. Rusted areas must be primed with Tremlite Metal Primer WB. Allow primer to become dry to touch prior to application of Tremlite Polyfoil Tape.

**Application:** Cut desired length of Tremlite Polyfoil with scissors or knife. Peel release liner from back and press into place. Press firmly starting at center and work toward outside edge with hand or small roller to insure complete adhesion. Be sure edges are tight, no fishmouths. Apply exactly first time, trying to remove may damage tape. **DO NOT STRETCH.** It is recommended, when pressing edges, use a cloth or glove to prevent "foil cuts" from the edge of the aluminum. Tremlite Polyfoil can be coated immediately with One Coat Aluminum, if desired. For vertical overlap seams (from peak to gutter) Tremlite Polyfoil Tape must be applied to the entire seam to insure water cannot wick under the material lap from areas at the top of the slope.

### COVERAGE

50 linear feet per roll. When applying over corrugated metal, be sure to calculate for irregular surfaces

### LIMITATIONS

- Apply at temperatures over 4° C (40° F)
- Do not apply over wet surfaces
- Rusted metal must be primed with Tremlite Metal
- Not recommended over standing seams or screwheads
- Not for application over asphalt mastics or other previously applied sealant materials.

# Tremlite Polyfoil

## PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUE	TEST METHOD
Peel Strength	10 lbs/linear inch (Adhesive)	ASTM D 3330-83
Low Temperature Flexibility	Passes, no cracking (Adhesive)	ASTM C 734
Tensile Strength	445 psi (60% elongation)	Adhesive (only)
Weather Resistance	2,000 hrs (QUV)	ASTM G 53

## MAINTENANCE

Your local Tremco Roofing sales representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

## PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

## TECHNICAL SUPPORT

Your local Tremco Roofing sales representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



[www.tremcoroofing.com](http://www.tremcoroofing.com)  
3735 Green Road  
Beachwood, Ohio 44122  
1.800.852.6013

220 Wicksteed Avenue  
Toronto, Ontario, M4H 1G7  
1.800.668.9879

Tremco Roofing and Building  
Maintenance is part of Tremco  
Construction Products Group.

Tremco is a US Registered trademark of Tremco CPG Inc.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.