

SAFETY DATA SHEET

1. Identification

Material name: GEOGARD® SEAM SEALER
Material: 49205

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Incorporated
3735 Green Road
BEACHWOOD OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 3
-------------------	------------

Health Hazards

Acute toxicity (Inhalation - vapor)	Category 3
Acute toxicity (Inhalation - dust and mist)	Category 4
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	12.58 %
Acute toxicity, dermal	19.91 %
Acute toxicity, inhalation, vapor	94.43 %
Acute toxicity, inhalation, dust or mist	97.06 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3
--	------------

Unknown toxicity - Environment

Acute hazards to the aquatic environment	90.16 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Flammable liquid and vapor.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
Harmful to aquatic life.

Precautionary Statements:

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor. Specific treatment (see this label). Wash contaminated clothing before reuse. In case of fire: Use ... to extinguish.

Storage: Store in well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result in GHS classification: Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium Carbonate (Limestone)	1317-65-3	10 - 30%
Xylene	1330-20-7	3 - 7%
Aromatic petroleum distillates	64742-95-6	3 - 7%
Titanium dioxide	13463-67-7	3 - 7%
1,2,4-Trimethylbenzene	95-63-6	1 - 5%
Aluminum	7429-90-5	1 - 5%
Hydrotreated heavy naphtha	64742-48-9	1 - 5%
Ethylbenzene	100-41-4	1 - 5%
1,3,5-Trimethylbenzene	108-67-8	0.5 - 1.5%
4,4'-Methylene bis(phenylisocyanate)	101-68-8	0.1 - 1%
Trimethyl benzene (mixed isomers)	25551-13-7	0.1 - 1%
Aluminum oxide	1344-28-1	0.1 - 1%
Cumene	98-82-8	0.1 - 1%
Polymethylene polyphenyl isocyanate	9016-87-9	0.1 - 1%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1%
2,4-Toluene diisocyanate	584-84-9	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up. Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m ³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)

	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
1,2,4-Trimethylbenzene	REL	25 ppm 125 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	TWA	25 ppm 125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	25 ppm 125 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL	25 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	140 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	ST ESL	700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	AN ESL	125 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	TWA PEL	25 ppm 125 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)
Aluminum - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Aluminum - Respirable dust. - as Al	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air

- as Al				Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphtha	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
1,3,5-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values (2011)
4,4'-Methylene bis(phenylisocyanate)	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
	Ceiling	0.02 ppm	0.2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Trimethyl benzene (mixed isomers)	TWA	25 ppm		US. ACGIH Threshold Limit Values (2011)
Aluminum oxide - Respirable fraction.	TWA		1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Total dust.	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Cumene	TWA	50 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	50 ppm	245 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
	Ceiling	0.02 ppm	0.2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA		2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA		0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Crystalline Silica (Quartz)/ Silica Sand - Total dust.	TWA		0.3 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
2,4-Toluene diisocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	0.02 ppm		US. ACGIH Threshold Limit Values (2011)
	Ceiling	0.02 ppm	0.14 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

			(02 2006)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Xylene	TWA	100 ppm	434 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm	651 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Aluminum - Respirable.	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum - Respirable fraction.	TWA	1 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Aluminum - Welding fume. - as Al	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Aluminum - as Al	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphtha	TWA	525 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Hydrotreated heavy naphtha	TWA	400 ppm	1,590 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
1,3,5-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
4,4'-Methylene bis(phenylisocyanate)	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
4,4'-Methylene bis(phenylisocyanate)	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

4,4'-Methylene bis(phenylisocyanate)	TWA	0.005 ppm	0.051 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Cumene	STEL	75 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cumene	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cumene	TWA	50 ppm	246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Polymethylene polyphenyl isocyanate	TWA	0.005 ppm	0.051 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA		0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
2,4-Toluene diisocyanate	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2,4-Toluene diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
2,4-Toluene diisocyanate	TWA	0.005 ppm	0.036 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	0.02 ppm	0.14 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection: Wear goggles/face shield.

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: liquid

Color: Gray

Odor: Mild petroleum/solvent

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: > 121 °C > 250 °F

Flash Point: 48 °C 119 °F(Setaflash Closed Cup)

Evaporation rate: Slower than Ether

Flammability (solid, gas): No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.195
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product:	ATEmix: 17,055.48 mg/kg
Dermal Product:	ATEmix: 7,993.4 mg/kg

Inhalation
Product: ATEmix: 8.62 mg/l
ATEmix: 2.06 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):

Xylene	in vivo (Rabbit): Experimental result, Weight of Evidence study
Aromatic petroleum distillates	in vivo (Rabbit): Experimental result, Key study
Titanium dioxide	in vivo (Rabbit): Experimental result, Supporting study
1,2,4-Trimethylbenzene	in vivo (Rabbit): Read-across from supporting substance (structural analogue or surrogate), Key study
Aluminum	in vivo (Rabbit): Read-across from supporting substance (structural analogue or surrogate), Supporting study
Hydrotreated heavy naphtha	in vivo (Rabbit): Experimental result, Supporting study
1,3,5-Trimethylbenzene	in vivo (Rabbit): Experimental result, Key study
4,4'-Methylene bis(phenylisocyanate)	in vivo (Rabbit): Read-across based on grouping of substances (category approach), Key study
Aluminum oxide	in vivo (Rabbit): Experimental result, Key study
Cumene	in vivo (Rabbit): Experimental result, Key study
2,4-Toluene diisocyanate	in vivo (Rabbit): Experimental result, Supporting study

Dibutyl tin dilaurate In vitro (Human, in vitro reconstituted epidermis model): Experimental result, Supporting study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
Aromatic petroleum distillates	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Titanium dioxide	in vivo (Rabbit, 24 hrs): Not irritating
1,2,4-Trimethylbenzene	in vivo (Rabbit, 30 min): Not irritating
Aluminum	in vivo (Rabbit, 24 hrs): Not irritating
Hydrotreated heavy naphtha	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Ethylbenzene	in vivo (Rabbit, 7 d): Slightly irritating
1,3,5-Trimethylbenzene	in vivo (Rabbit, 30 min): Not irritating
4,4'-Methylene bis(phenylisocyanate)	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Trimethyl benzene (mixed isomers)	Irritating
Aluminum oxide	in vivo (Rabbit, 24 hrs): Not irritating
Cumene	in vivo (Rabbit, 24 hrs): Not irritating
2,4-Toluene diisocyanate	in vivo (Rabbit, 24 - 72 hrs): Category 2
Dibutyl tin dilaurate	in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Cumene	Overall evaluation: Possibly carcinogenic to humans.
Crystalline Silica (Quartz)/ Silica Sand	Overall evaluation: Carcinogenic to humans.
2,4-Toluene diisocyanate	Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Cumene	Reasonably Anticipated to be a Human Carcinogen.
Crystalline Silica (Quartz)/ Silica Sand	Known To Be Human Carcinogen.
2,4-Toluene diisocyanate	Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene	LC 50 (Bryconamericus iheringii, 96 h): 9.94 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study LC 50 (Oncorhynchus mykiss, 96 h): 8.05 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study LC 50 (Bryconamericus iheringii, 96 h): 6.9 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study LC 50 (Oncorhynchus mykiss, 96 h): 7.6 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study LC 50 (Oncorhynchus mykiss, 96 h): 2.6 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study
1,2,4-Trimethylbenzene	LC 50 (Various, 96 h): 3.41 mg/l QSAR QSAR, Supporting study LC 50 (Oryzias latipes, 48 h): 18 mg/l Experimental result, Supporting study LC 50 (Oncorhynchus mykiss): 9.22 mg/l Not specified, Not specified LC 50 (Pimephales promelas, 96 h): 7.72 mg/l Experimental result, Key study LC 50 (Pimephales promelas, 96 h): 7.72 mg/l
Ethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.5 - 11 mg/l Mortality
1,3,5-Trimethylbenzene	LC 50 (Goldfish (Carassius auratus), 96 h): 9.89 - 15.05 mg/l Mortality
Cumene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 6.04 - 6.61 mg/l Mortality
2,4-Toluene diisocyanate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 108.8 - 240.4 mg/l Mortality
Dibutyl tin dilaurate	LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Xylene	EC 50 (Daphnia magna, 48 h): 3.82 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study EC 50 (Ceriodaphnia dubia, 48 h): > 3.4 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study IC 50 (Daphnia magna, 24 h): 4.7 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study IC 50 (Daphnia magna, 24 h): 3.6 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study IC 50 (Daphnia magna, 24 h): 2.2 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study
--------	--

Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication
1,2,4-Trimethylbenzene	LC 50 (Artemia sp., 24 h): 12 mg/l Experimental result, Supporting study LC 50 (Artemia sp., 48 h): 3.6 mg/l Experimental result, Supporting study LC 50 (Americamysis bahia, 96 h): +/- +/- 2 mg/l Not specified, Not specified LC 50 (Daphnia sp., 48 h): 2.446 mg/l QSAR QSAR, Supporting study EC 50 (Daphnia magna, 48 h): +/- +/- 6.14 mg/l Not specified, Not specified
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication
1,3,5-Trimethylbenzene	EC 50 (Water flea (Daphnia magna), 24 h): 50 mg/l Intoxication
Trimethyl benzene (mixed isomers)	LC 50 (Daggerblade grass shrimp (Palaemonetes pugio), 24 h): 7 mg/l Mortality
Cumene	LC 50 (Water flea (Daphnia magna), 24 h): 95 mg/l Mortality
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Aromatic petroleum distillates	EC 50 (Daphnia magna, 21 d): 10 mg/l Other, Key study
Titanium dioxide	LC 50 (Oncorhynchus mykiss, 28 d): 7.31 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study
Aluminum	EC 10 (Pimephales promelas, 7 d): 0.481 mg/l Experimental result, Weight of Evidence study EC 10 (Pimephales promelas, 7 d): 0.726 mg/l Experimental result, Weight of Evidence study EC 10 (Pimephales promelas, 7 d): 0.457 mg/l Experimental result, Weight of Evidence study NOAEL (Salvelinus fontinalis, 60 d): > 0.35 mg/l Experimental result, Weight of Evidence study LOAEL (Pimephales promelas, 7 d): >= 0.831 mg/l Experimental result, Weight of Evidence study
Hydrotreated heavy naphtha	LL 50 (Pimephales promelas, 14 d): 5.2 mg/l Experimental result, Supporting study NOAEL (Pimephales promelas, 14 d): 2.6 mg/l Experimental result, Supporting study NOAEL (Daphnia magna, 21 d): 2.6 mg/l Other, Key study EC 50 (Daphnia magna, 21 d): 10 mg/l Other, Key study
Cumene	NOAEL (Danio rerio; Pimephales promelas, 28 d): 0.38 mg/l QSAR QSAR, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Xylene
NOAEL (Ceriodaphnia dubia, 7 d): 1.17 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study
NOAEL (Daphnia magna, 21 d): 1.57 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study
LOAEL (Daphnia magna, 21 d): 3.16 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study
EC 10 (Daphnia magna, 21 d): 1.91 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study
EC 50 (Daphnia magna, 21 d): 2.9 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study

**Toxicity to Aquatic Plants
Product:**

No data available.

Persistence and Degradability

**Biodegradation
Product:**

No data available.

**BOD/COD Ratio
Product:**

No data available.

Bioaccumulative Potential

**Bioconcentration Factor (BCF)
Product:**

No data available.

Specified substance(s):

Xylene

Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 5.5 - < 12.2 Aquatic sediment Experimental result, Key study
Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 8.1 - < 25.9 Aquatic sediment Experimental result, Key study
Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 7.2 - < 24.2 Aquatic sediment Experimental result, Key study
Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 7.4 - < 18.5 Aquatic sediment Experimental result, Key study
Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 7.7 - < 21.2 Aquatic sediment Experimental result, Key study

1,2,4-Trimethylbenzene

Pimephales promelas, Bioconcentration Factor (BCF): 243 Aquatic sediment QSAR, Key study
Cyprinus carpio, Bioconcentration Factor (BCF): 31 - 207 Aquatic sediment Experimental result, Supporting study
Cyprinus carpio, Bioconcentration Factor (BCF): 33 - < 275 Aquatic sediment Experimental result, Supporting study

Aluminum

Brook trout (Salvelinus fontinalis), Bioconcentration Factor (BCF): 36 (Flow through)

**Partition Coefficient n-octanol / water (log Kow)
Product:**

No data available.

Specified substance(s):

Xylene

Log Kow: 3.12 - 3.20

Ethylbenzene	Log Kow: 3.15
Cumene	Log Kow: 3.66
Dibutyl tin dilaurate	Log Kow: 3.12

Mobility in Soil: No data available.

Other Adverse Effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

UN1139, COATING SOLUTION, 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity

2,4-Toluene diisocyanate

Reportable quantity

De minimis concentration: 0.1% One-Time Export Notification only.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
4,4'-Methylene bis(phenylisocyanate)	5000 lbs.
Cumene	5000 lbs.
Polymethylene polyphenyl isocyanate	5000 lbs.
2,4-Toluene diisocyanate	100 lbs.
Toluene	1000 lbs.
Toluene-2,6-Diisocyanate	100 lbs.
Naphthalene	100 lbs.
Benzene	10 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Fire Hazard
- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
2,4-Toluene diisocyanate	100 lbs.	500 lbs.
Toluene-2,6-Diisocyanate	100 lbs.	100 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
4,4'-Methylene bis(phenylisocyanate)	5000 lbs.
Cumene	5000 lbs.
Polymethylene polyphenyl isocyanate	5000 lbs.
2,4-Toluene diisocyanate	100 lbs.
Toluene	1000 lbs.
Toluene-2,6-Diisocyanate	100 lbs.
Naphthalene	100 lbs.
Benzene	10 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
2,4-Toluene diisocyanate	500lbs
Toluene-2,6-Diisocyanate	100lbs
Calcium Carbonate (Limestone)	500 lbs
Xylene	500 lbs
Aromatic petroleum distillates	500 lbs
Titanium dioxide	500 lbs
1,2,4-Trimethylbenzene	500 lbs
Aluminum	500 lbs
Hydrotreated heavy naphtha	500 lbs
Ethylbenzene	500 lbs
1,3,5-Trimethylbenzene	500 lbs
4,4'-Methylene bis(phenylisocyanate)	500 lbs
Trimethyl benzene (mixed isomers)	500 lbs
Aluminum oxide	500 lbs
Cumene	500 lbs
Polymethylene polyphenyl isocyanate	500 lbs
Crystalline Silica (Quartz)/ Silica Sand	500 lbs
Dibutyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Xylene
1,2,4-Trimethylbenzene
Aluminum
Ethylbenzene
2,4-Toluene diisocyanate

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2,4-Toluene diisocyanate	10000 lbs
Toluene-2,6-Diisocyanate	10000 lbs

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
1,2,4-Trimethylbenzene
Aluminum
Hydrotreated heavy naphtha
Ethylbenzene
Crystalline Silica (Quartz)/ Silica Sand
2,4-Toluene diisocyanate

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
1,2,4-Trimethylbenzene
Aluminum
Hydrotreated heavy naphtha
Ethylbenzene
Crystalline Silica (Quartz)/ Silica Sand
2,4-Toluene diisocyanate
Toluene-2,6-Diisocyanate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Calcium Carbonate (Limestone)
Xylene
Titanium dioxide
1,2,4-Trimethylbenzene
Aluminum
Hydrotreated heavy naphtha
Ethylbenzene
2,4-Toluene diisocyanate

US. Rhode Island RTK

Chemical Identity

Xylene
1,2,4-Trimethylbenzene
Aluminum
Ethylbenzene

Other Regulations:

Regulatory VOC (less water and exempt solvent):	189 g/l
VOC Method 310:	15.78 %

Inventory Status:

Australia AICS:

One or more components in this product are not listed on or exempt from the Inventory.

Canada DSL Inventory List:

One or more components in this product are

	not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision**Revision Date:** 09/28/2016**Version #:** 2.1**Further Information:** No data available.**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.