

SAFETY DATA SHEET

1. Identification

Material name: Solargard[®] Masonry Primer
Material: 1110700001

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S. Roofing
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A
Toxic to reproduction	Category 1B

Unknown toxicity - Health

Acute toxicity, oral	48.21 %
Acute toxicity, dermal	53.89 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	92.09 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3
------------------------------------------	------------

Unknown toxicity - Environment

Acute hazards to the aquatic environment	77.94 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	Harmful if inhaled. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Harmful to aquatic life.
Precautionary Statement:	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	7 - 13%
Propylene glycol	57-55-6	5 - 10%
Zinc oxide	1314-13-2	3 - 7%
Titanium dioxide	13463-67-7	3 - 7%
Talc	14807-96-6	1 - 5%
Heavy paraffinic distillate	64741-88-4	0.1 - 1%
Amorphous silica	7631-86-9	0.1 - 1%
n-(3,4-dichlorophenyl)-n,n-dimethylurea	330-54-1	0.1 - 1%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1%
Kaolin Clay	1332-58-7	0.1 - 1%
Aluminum hydroxide	21645-51-2	0.1 - 1%
Aluminum oxide	1344-28-1	0.1 - 1%
Methyl benzimidazole-2-yl	10605-21-7	0.1 - 1%

carbamate		
Magnesite	546-93-0	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Rinse mouth thoroughly.
- Inhalation:** Move to fresh air.
- Skin Contact:** Remove contaminated clothing and wash the skin thoroughly with soap and water after work.
- Eye contact:** Rinse immediately with plenty of water.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: No data available.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Respirable fraction.	TWA	2 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	STEL	10 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Zinc oxide - Fume.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Talc - Respirable fraction.	TWA	2 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Talc	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Talc - Respirable.	TWA	2.4	US. OSHA Table Z-3 (29 CFR

		millions of particles per cubic foot of air	1910.1000) (2000)
	TWA	0.1 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Talc - Total dust.	TWA	0.3 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Heavy paraffinic distillate - Inhalable fraction.	TWA	5 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Heavy paraffinic distillate	PEL	500 ppm 2,000 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Heavy paraffinic distillate - Mist.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Amorphous silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
n-(3,4-dichlorophenyl)-n,n-dimethylurea	TWA	10 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Crystalline Silica (Quartz)/ Silica Sand - Total dust.	TWA	0.3 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Kaolin Clay - Respirable fraction.	TWA	2 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Kaolin Clay - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum hydroxide - Respirable fraction.	TWA	1 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air

			Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Propylene glycol - Aerosol.	TWAEV	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Propylene glycol - Vapor and aerosol, inhalable fraction.	TWAEV	50 ppm 155 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zinc oxide - Respirable.	TWA	2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Zinc oxide - Respirable fraction.	TWAEV	2 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Zinc oxide - Fume.	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zinc oxide - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zinc oxide - Fume.	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Talc - Respirable.	TWA	2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Talc - Respirable particles.	TWAEV	2 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Talc	TWAEV	2 fibers/mL	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Talc - Respirable dust.	TWA	3 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Heavy paraffinic distillate - Mist.	TWA	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Heavy paraffinic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Heavy paraffinic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWAEV	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

- General information:** Use personal protective equipment as required.
- Eye/face protection:** Wear goggles/face shield.
- Skin Protection**
 - Hand Protection:** Use suitable protective gloves if risk of skin contact.
 - Other:** No data available.
- Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
- Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use.

9. Physical and chemical properties

Appearance

- Physical state:** liquid
- Form:** liquid

Color:	White
Odor:	Mild
Odor threshold:	No data available.
pH:	9.5
Melting point/freezing point:	-0.00 °C 32 °F
Initial boiling point and boiling range:	100 °C 212 °F
Flash Point:	No data available.
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.46
Solubility(ies)	
Solubility in water:	Soluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of Hazardous Reactions:	No data available.
Conditions to Avoid:	Avoid heat or contamination.
Incompatible Materials:	Strong acids. Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact: Moderately irritating to skin with prolonged exposure.

Eye contact: Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: No data available.

Dermal

Product: ATEmix: 5,251.52 mg/kg

Inhalation

Product: ATEmix: 3.34 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Propylene glycol	(Human): Irritating
Zinc oxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Heavy paraffinic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Amorphous silica	in vivo (Rabbit, 24 hrs): Not irritating
n-(3,4-dichlorophenyl)-n,n-dimethylurea	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Aluminum hydroxide	in vivo (Rabbit, 24 hrs): Not irritating
Aluminum oxide	in vivo (Rabbit, 24 hrs): Not irritating
Magnesite	In vitro (Reconstituted Corneal Epithelium model, 10 min): Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity**Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Talc	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Possibly carcinogenic to humans.
Heavy paraffinic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.
Crystalline Silica (Quartz)/ Silica Sand	Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Heavy paraffinic distillate	Known To Be Human Carcinogen.
Crystalline Silica (Quartz)/ Silica Sand	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity**In vitro**
Product: No data available.**In vivo**
Product: No data available.**Reproductive toxicity****Product:** May damage fertility or the unborn child.**Specific Target Organ Toxicity - Single Exposure****Product:** No data available.**Specific Target Organ Toxicity - Repeated Exposure****Product:** No data available.**Aspiration Hazard****Product:** No data available.**Other effects:** No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:	No data available.
Specified substance(s):	
Calcium carbonate	LC 50 (Western mosquitofish (<i>Gambusia affinis</i>), 96 h): > 56,000 mg/l Mortality
Propylene glycol	LC 50 (Fathead minnow (<i>Pimephales promelas</i>), 96 h): 55,770 mg/l Mortality
Zinc oxide	LC 50 (Fathead minnow (<i>Pimephales promelas</i>), 96 h): 2,246 mg/l Mortality
Titanium dioxide	LC 50 (Mummichog (<i>Fundulus heteroclitus</i>), 96 h): > 1,000 mg/l Mortality

Aquatic Invertebrates

Product:	No data available.
Specified substance(s):	
Propylene glycol	EC 50 (Water flea (<i>Daphnia magna</i>), 48 h): > 10,000 mg/l Intoxication EC 50 (Water flea (<i>Daphnia magna</i>), 24 h): > 10,000 mg/l Intoxication LC 50 (Brine shrimp (<i>Artemia salina</i>), 24 h): > 10,000 mg/l Mortality
Zinc oxide	LC 50 (Water flea (<i>Daphnia magna</i>), 48 h): 24.6 mg/l Mortality
Titanium dioxide	EC 50 (Water flea (<i>Daphnia magna</i>), 48 h): > 1,000 mg/l Intoxication
n-(3,4-dichlorophenyl)- n,n-dimethylurea	LC 50 (Northern quahog or hard clam (<i>Mercenaria mercenaria</i>), 12 d): > 5 mg/l Mortality LC 50 (Water flea (<i>Daphnia pulex</i>), 3 h): > 40 mg/l Mortality LC 50 (Water flea (<i>Moina macrocopa</i>), 3 h): > 40 mg/l Mortality
Methyl benzimidazole-2- yl carbamate	LC 50 (Water flea (<i>Daphnia magna</i>), 48 h): 0.38 - 0.56 mg/l Mortality LC 50 (Dungeness or edible crab (<i>Cancer magister</i>), 48 h): > 100 mg/l Mortality

Chronic hazards to the aquatic environment:

Fish

Product:	No data available.
Specified substance(s):	
Propylene glycol	NOAEL (<i>Pimephales promelas</i> , 7 d): 11,530 mg/l experimental result
Zinc oxide	NOAEL (<i>Oncorhynchus mykiss</i> , 30 d): 974 µg/l interpreted
Titanium dioxide	LC 0 (<i>Coregonus autumnalis migratorius</i> G., 30 d): 3 mg/l experimental result
Heavy paraffinic distillate	NOAEL (<i>Oncorhynchus mykiss</i> , 14 d): >= 1,000 mg/l QSAR
n-(3,4-dichlorophenyl)-	LC 50 (<i>Oncorhynchus mykiss</i> , 28 d): 4.01 mg/l experimental result

n,n-dimethylurea

Aluminum hydroxide LOAEL (Pimephales promelas, 28 d): 53.8 mg/l experimental result

Aluminum oxide NOAEL (Pimephales promelas, 28 d): 4.7 mg/l experimental result

Aquatic Invertebrates**Product:** No data available.**Toxicity to Aquatic Plants****Product:** No data available.**Persistence and Degradability****Biodegradation****Product:** No data available.**BOD/COD Ratio****Product:** No data available.**Bioaccumulative Potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Propylene glycol Log Kow: -0.92

n-(3,4-dichlorophenyl)-
n,n-dimethylurea Log Kow: 2.68Methyl benzimidazole-2-
yl carbamate Log Kow: 1.52**Mobility in Soil:** No data available.**Other Adverse Effects:** Harmful to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

800000052455

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
n-(3,4-dichlorophenyl)- n,n-dimethylurea	100 lbs.
Methyl benzimidazole-2- yl carbamate	10 lbs.
Ammonia	100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards

Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Ammonia	100 lbs.	500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Zinc oxide	
n-(3,4-dichlorophenyl)- n,n-dimethylurea	100 lbs.
Methyl benzimidazole-2- yl carbamate	10 lbs.
Ammonia	100 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Ammonia	500lbs
Calcium carbonate	500 lbs
Propylene glycol	500 lbs
Zinc oxide	500 lbs
Titanium dioxide	500 lbs
Talc	500 lbs
Heavy paraffinic distillate	500 lbs
Amorphous silica	500 lbs
n-(3,4-dichlorophenyl)-n,n-dimethylurea	500 lbs
Crystalline Silica (Quartz)/ Silica Sand	500 lbs
Kaolin Clay	500 lbs
Aluminum hydroxide	500 lbs
Aluminum oxide	500 lbs
Methyl benzimidazole-2-yl carbamate	500 lbs
Magnesite	500 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Zinc oxide

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Ammonia	10000 lbs
Ammonia	20000 lbs

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

<u>Chemical Identity</u>
Calcium carbonate
Propylene glycol
Zinc oxide
Titanium dioxide
Talc

US. Massachusetts RTK - Substance List

<u>Chemical Identity</u>
Calcium carbonate
Zinc oxide
Titanium dioxide
Talc
Crystalline Silica (Quartz)/ Silica Sand
Ammonia

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Calcium carbonate
Propylene glycol
Zinc oxide
Titanium dioxide
Talc

US. Rhode Island RTK

Chemical Identity

Zinc oxide

Other Regulations:

Regulatory VOC (less water and exempt solvent):	95 g/l
VOC Method 310:	2.47 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision**Revision Date:** 08/14/2015**Version #:** 1.0**Further Information:** No data available.**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

