

GEOGARD® Seam Sealer

#49205 - 5 gallon pail
#49201 - 1 gallon
container (4 per case)

Polyurethane sealer

Description

GEOGARD Seam Sealer is a single component, high solids moisture curing, polyurethane sealer formulated to provide a tough, flexible film for waterproofing a variety of roofing substrates including metal, weathered single ply, built-up, modified bitumen, polyurethane foam and concrete.

Uses

GEOGARD Seam Sealer provides a waterproof patch for seams and metal fasteners. It can also be used to seal joints in copings, flashings, vents and parapet walls, and may be applied to other protrusions on a variety of roofing surfaces. It can be used with PERMAFAB fabric in areas of high stress.

Advantages

GEOGARD Seam Sealer provides a quick, durable waterproofing seal that is easy to apply. It can be used as a stand alone sealant or in conjunction with Republic coating systems. GEOGARD Seam Sealer can be used at temperatures down to 30°F.

Limitations

Do not apply when air or surface temperature is below 30°F or when rain is imminent. Do not apply over damp or frosted surfaces. Not intended for service over tar, silicone based caulks or coatings, or below grade. This product is a moisture cured urethane. Once opened, if any coating has skinned on surface of pail, remove it. DO NOT MIX IT INTO REMAINING COATING.

Coverage

Approx. 60-100 lineal feet per gallon @ 1/8" thick in a width of 4" - 6".

Approx. 30-40 lineal feet per gallon when three coursing using PERMAFAB fabric.

Approx. 200 fasteners per gallon @ 1/8" thick.

The surface dictates the actual coverage needed.

Preparation

All surfaces must be clean and free from dirt, grease, oil, loose gravel, loose paint, rust, excess chalk and other foreign matter which could prevent proper adhesion. This is best accomplished using a high pressure wash of at least 2,000 psi.

If surface was previously coated, please contact the Republic Technical Department for surface preparation recommendations.

Application

Apply GEOGARD Seam Sealer by brush working material into overlaps and around fasteners to completely encapsulate. PERMAFAB fabric should be incorporated into the repair for areas of high stress including flashings. GEOGARD Seam Sealer can be used as a stand alone sealant or in conjunction with Republic coating systems. Allow to completely dry before top coating. If left uncoated for more than 72 hours, GEOGARD Primer may need to be used to reactivate GEOGARD Seam Sealer prior to applying a Republic coating system. Environmental conditions with extremes in temperature and humidity may affect cure rates.

Refer to appropriate application specifications for additional information.

Maintenance

It is recommended that the system be checked on a regular schedule with additional inspections after the system has been exposed to severe conditions. Small area touch up can be made at any time by following recommended application procedures.

Technical Services

Technical advice or service on suitability of material for specific application and end-use requirements is available from the manufacturer. Refer to label and Material Safety Data Sheet (MSDS) for precautionary information.

TECHNICAL DATA

Weight per Gallon (ASTM D 1475) 10.5 lbs.

Solids by Volume 80%

Elongation (ASTM D 412) 220%

Tensile Strength (ASTM D 412) 270 psi

Dry Time (ASTM D 1640) 24 hours to tack free

Flashpoint (Seta Flash) 119°F

Clean Up Republic Thinner #1 or Xylene

Shelf Life Approx. 6 months in an unopened container



REPUBLIC
RESTORATION SYSTEMS

TREMCO

GEOGARD® Seam Sealer



Tremco Incorporated
3735 Green Road, Beachwood, OH 44122
U.S.: 800-551-7081
50 Beth Nealson Drive, Toronto, Ontario M4H 1M6
CA: 800-668-9879
www.rpmrepublic.com



GEOGARD is a U.S. registered trademark of Republic Powdered Metals, Inc.

The information provided on this data sheet is effective as of September 2013 and supersedes all previous data concerning this product and its application.

© Republic Restoration Systems by Tremco, 2013. All Rights Reserved.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.