

PERMAFAB

#230004R – 4" x 300 roll
#230006R – 6" x 300 roll
#230012R – 12" x 300 roll
#290400 – 40" x 324 roll

Polyester fabric

Description

PERMAFAB is 100% stitchbonded, polyester fabric that offers an unusual combination of high strength properties with good elongation for excellent resistance against thermal stress.

Uses

PERMAFAB is designed to be used in conjunction with Tremco restoration coatings and sealants in restoration, maintenance, and repair applications.

Advantages

PERMAFAB polyester fabric will not rot as it ages and it is resistant to moisture.

Limitations

Application temperature shall be above 40°F. Do not apply when rain is imminent. Not to be directly embedded into any aluminum based coatings.

Coverage

One roll of PERMAFAB will cover:

40" ↔ 324 1,101 sq. ft. (gross) (11.0 squares)

A single overlayment with:

4" overlap 972 sq. ft. (net) (9.7 squares)

Application

Refer to the following Product Data Sheets and/or substrate specific general guideline specifications for complete application information.

Maintenance

It is recommended that the coating installation be checked on a regular schedule with additional inspections after the system has been exposed to severe weather conditions. Recoating or small area touch-up can be made at any time by following recommended application procedures.

TECHNICAL DATA

Weight per Sq. Yd	3 oz.
Weight per Roll	33 lbs. (40" roll)
Elongation (ASTM D 1682)	61.65% avg.*
Tensile (ASTM D 1682)	51.1 lbs. avg.*
Mullen Burst (ASTM D 3786)	176.8 lbs.
Trapezoid (ASTM D 1117) (Tear Strength)	16.1 lbs. avg.*
Mildew & Rot Resistance	Excellent

*NOTE: Average machine & cross machine direction.

Technical Services

Technical advice or service on suitability of material for specific application and end-use requirements is available from the manufacturer. Refer to label and Material Safety Data Sheet (MSDS) for precautionary information.



REPUBLIC
RESTORATION SYSTEMS

TREMCO

PERMAFAB



Tremco Incorporated
3735 Green Road, Beachwood, OH 44122
U.S.: 800-551-7081
50 Beth Nealson Drive, Toronto, Ontario M4H 1M6
CA: 800-668-9879
www.rpmrepublic.com

PERMAFAB is a U.S. registered trademark of Republic Powdered Metals, Inc.

The information provided on this data sheet is effective as of September 2013 and supersedes all previous data concerning this product and its application.

© Republic Restoration Systems by Tremco, 2013. All Rights Reserved.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.