

SKYLIGHT COATING Clear

CLEAR

110705 – 5 gallon pails

110701 – 1 gallon cans (4 per case)

Acrylic Coating

Description

SKYLIGHT COATING Clear is a translucent clear acrylic coating. It is formulated from durable 100% acrylic resins with excellent weathering and UV resistance specifically for use on weathered fiberglass skylight panels.

Uses

Through weathering, the resinous binder sealing the fiberglass filaments wears away exposing raw strands of glass that collect dirt and debris, eventually cutting out light and taking away much of the panel's original translucent value. SKYLIGHT COATING Clear binds and seals these fibers providing a tough, durable weather resistant finish. SKYLIGHT COATING Clear will restore the panel to its original gloss and color. Light entrance is permitted while it filters out ultraviolet rays.

Limitations

For industrial use only. SKYLIGHT COATING Clear is to be applied to fiberglass skylights. Do not apply over any other surface or substrate. Application temperature shall be above 50°F. Do not apply when rain is imminent.

Coverage

SKYLIGHT COATING Clear should be applied at the rate of 300 sq. ft./gal. The surface dictates the actual coverage. The amount shown above is intended as minimum application information.

Preparation

Vigorously brush the panel surface with water and light detergent. Rinse with clear water, making sure the surface is clean from dirt and debris.

Application

The surface may be slightly damp but should not be wet. Spray, brush or roller apply. For better performance and greater longevity, two coats are recommended. Do not apply when rain is forecast within 4 hours of application.

Maintenance

It is recommended that the coated area be checked on a regular schedule with additional inspections after the system has been exposed to severe weather conditions. Recoating or small area touch up can be made at any time by following recommended application procedures.

Technical Services

Technical advice or service on suitability of material for specific application and end-use requirements is available from the manufacturer. Refer to label and Safety Data Sheet (SDS) for precautionary information.

TECHNICAL DATA

Weight per Gallon (ASTM D 1475)	9.3 ± 0.2 lbs.
Specific Gravity (ASTM D 1475)	1.12 ± 0.02
Solids by Volume	39% ± 1%
Solids by Weight	45% ± 1%
Viscosity (ASTM D 562)	70–75 KU
Dry Time	1/2 – 1 hour
Flashpoint (ASTM D 3278)	None
Clean Up	Soap and water



REPUBLIC
RESTORATION SYSTEMS

TREMCO

SKYLIGHT COATING Clear



Tremco Incorporated
3735 Green Road, Beachwood, OH 44122
U.S.: 800-551-7081
50 Beth Nealsen Drive, Toronto, Ontario M4H 1M6
CA: 800-668-9879
www.tremcoroofing.com

The information provided on this data sheet is effective as of May 2016 and supersedes all previous data concerning this product and its application.

© Republic Restoration Systems by Tremco, 2016. All Rights Reserved.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.