

# SOLARGARD® MASONRY PRIMER

#1110700005-5 gallon pail

#1110700001 - 1 gallon container (4 per case)

## Acrylic Primer

### Description

SOLARGARD MASONRY PRIMER is a high quality, acrylic primer formulated from 100% acrylic resins. SOLARGARD MASONRY PRIMER bonds firmly to brick, stone, concrete, plaster, stucco, and other cementitious surfaces.

### Uses

SOLARGARD MASONRY PRIMER is an ideal primer for brick, stone, concrete, plaster, stucco, and other cementitious surfaces. It may also be used to prime wood. SOLARGARD MASONRY PRIMER may be used on porous surfaces prior to application of SOLARGARD HY-BUILD.

### Advantages

SOLARGARD MASONRY PRIMER bonds firmly to cementitious surfaces providing for excellent adhesion of the coating to the substrate.

### Limitations

Application temperature shall be above 50°F. Protect from freezing. Not intended for immersion service or over tar, glazed tile, silicone based coatings, or below grade. SOLARGARD MASONRY PRIMER must be top-coated with SOLARGARD HY-BUILD within 72 hours.

### Coverage

Applied as a single coat over brick, stone, concrete, plaster, stucco, and other cementitious surfaces, SOLARGARD MASONRY PRIMER will cover approximately 100-200 sq. ft./gal. The porosity of the surface to be coated may cause coverage to vary.

### Preparation

All surfaces are to be free of dirt, grease, oil, chalk, loose paint, rust, mortar, and other foreign matter, which could prevent proper adhesion. This is best accomplished using a high pressure power wash of at least 2,000 psi. A surface cleaner shall be used to remove all grease or oily deposits.

**Masonry, Brick, Concrete, and Stucco:** If surface is previously coated, contact Republic Technical Department for surface preparation recommendations. Masonry repairs should be completed and the cement allowed to dry before "spot priming" with SOLARGARD MASONRY PRIMER.

**Wood:** New or unpainted wood surfaces require two coats of SOLARGARD MASONRY PRIMER.

### Application

SOLARGARD MASONRY PRIMER shall be applied by brush, roller, or paint spray equipment. Mix well to obtain uniform color.

When SOLARGARD MASONRY PRIMER has been applied longer than 72 hours prior to application of SOLARGARD HY-BUILD, SOLARGARD MASONRY PRIMER is to be reapplied. All surfaces, which have been primed, must be clean and free of dirt, grease, oil and other foreign matter, which could prevent proper adhesion of SOLARGARD HY-BUILD.

### Maintenance

It is recommended that the coating application be checked on a regular schedule with additional inspections after the system has been exposed to severe weather conditions. Recoating or small area touch up can be made at any time by following recommended application procedures.

### Technical Services

Technical advice or service on suitability of material for specific application and end-use requirements is available from the manufacturer. Refer to label and Material Safety Data Sheet (MSDS) for precautionary information.

### TECHNICAL DATA

<b>Weight per Gallon (ASTM D 1475)</b>	12.1±0.2 lbs.
<b>Solids by Volume</b>	41% ± 1%
<b>Solids by Weight</b>	59% ± 1%
<b>Viscosity @ 77°F (ASTM D 562)</b>	75 KU ± 1KU
<b>Abrasion Resistance</b>	Excellent
<b>Flexibility (ASTM D 1737)</b>	Pass 1/8" mandrel bend
<b>Dry Time</b>	1 hour to dust free 2 hours to tack free Overnight to hard
<b>Flashpoint (ASTM D 3278)</b>	None
<b>Gloss 60° on Gardner Glossgard (ASTM D 523)</b>	12° ± 5
<b>Clean Up</b>	Soap & water
<b>VOC</b>	62 g/l



# SOLARGARD® MASONRY PRIMER

---



**Tremco Incorporated**  
3735 Green Road, Beachwood, OH 44122  
**U.S.: 800-551-7081**  
50 Beth Nealson Drive, Toronto, Ontario M4H 1M6  
**CA: 800-668-9879**  
**[www.tremcoroofing.com](http://www.tremcoroofing.com)**

---

SOLARGARD is a U.S. registered trademark of Republic Powdered Metals, Inc.

The information provided on this data sheet is effective as of January 2014 and supersedes all previous data concerning this product and its application.

© Republic Restoration Systems by Tremco, 2013. All Rights Reserved.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.