

Version: 1.0 Revision Date: 08/17/2015

SAFETY DATA SHEET

1. Identification

Material name: SOLARGARD H.B. SCC HONEY TWIST 5 GL Material: 1512042805P

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S. Roofing 3735 Green Road Cleveland OH 44122 US

Contact person: Telephone: Emergency telephone number:

EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

| Health Hazards | |
|---|-------------|
| Acute toxicity (Inhalation - dust and mist) | Category 4 |
| Carcinogenicity | Category 1A |
| Unknown toxicity - Health | |
| Acute toxicity, oral | 34.62 % |
| Acute toxicity, dermal | 39.54 % |
| Acute toxicity, inhalation, vapor | 100 % |
| Acute toxicity, inhalation, dust or mist | 73.64 % |
| Unknown toxicity - Environment | |
| Acute hazards to the aquatic environment | 64.63 % |
| Chronic hazards to the aquatic environment | 100 % |

Label Elements

Hazard Symbol:



Danger

Signal Word:

Hazard Statement:

Harmful if inhaled. May cause cancer.



| Precautionary Statement: | |
|--|---|
| Prevention: | Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. |
| Response: | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. |
| Storage: | Store locked up. |
| Disposal: | Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. |
| Other hazards which do not result in GHS classification: | None. |

3. Composition/information on ingredients

Mixtures

| Chemical Identity | CAS number | Content in percent (%)* |
|---|------------|-------------------------|
| Calcium carbonate | 471-34-1 | 15 - 40% |
| Titanium dioxide | 13463-67-7 | 3 - 7% |
| Propylene glycol | 57-55-6 | 1 - 5% |
| Zinc oxide | 1314-13-2 | 1 - 5% |
| ** | ** | 1 - 5% |
| Clay | 1332-58-7 | 0.1 - 1% |
| Magnesite | 546-93-0 | 0.1 - 1% |
| Aluminum oxide | 1344-28-1 | 0.1 - 1% |
| Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 | 0.1 - 1% |
| Ammonium hydroxide | 1336-21-6 | 0.1 - 1% |
| Talc | 14807-96-6 | 0.1 - 1% |

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Trade secret information:

** A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

| 4. First-aid measures | |
|-----------------------|---|
| Ingestion: | Call a POISON CENTER/doctor//if you feel unwell. Rinse mouth. |
| Inhalation: | Move to fresh air. |
| Skin Contact: | Wash skin thoroughly with soap and water. Get medical attention if symptoms occur. |
| Eye contact: | Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention. |
| | 2/18 |



| Most important symptoms/effect | s, acute and delayed |
|--|---|
| Symptoms: | May cause skin and eye irritation. |
| Indication of immediate medical a | ttention and special treatment needed |
| Treatment: | Symptoms may be delayed. |
| 5. Fire-fighting measures | |
| General Fire Hazards: | No unusual fire or explosion hazards noted. |
| Suitable (and unsuitable) ex | ktinguishing media |
| Suitable extinguishing media: | Use fire-extinguishing media appropriate for surrounding materials. |
| Unsuitable extinguishing media: | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical: | During fire, gases hazardous to health may be formed. |
| Special protective equipment an | d precautions for firefighters |
| Special fire fighting procedures: | No data available. |
| Special protective equipment for fire-fighters: | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| 6. Accidental release measures | s |
| Personal precautions, protective equipment and emergency procedures: | No data available. |
| Methods and material for containment and cleaning up: | Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. |
| Notification Procedures: | In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. |
| Environmental Precautions: | Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. |



7. Handling and storage

| Precautions for safe handling: | Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. |
|---|--|
| Conditions for safe storage, including any incompatibilities: | Store locked up. |

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

| Chemical Identity | type | Exposure Limit Values | Source |
|---|------|-----------------------|---|
| Calcium carbonate - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Calcium carbonate - Respirable fraction. | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Titanium dioxide | TWA | 10 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| Titanium dioxide - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Zinc oxide - Respirable fraction. | TWA | 2 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| | STEL | 10 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| Zinc oxide - Fume. | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Zinc oxide - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Zinc oxide - Respirable fraction. | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| ** | TWA | 10 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Clay - Respirable fraction. | TWA | 2 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Clay - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air |



| | | | Contaminants (29 CFR 1910.1000) (02 2006) |
|---|------|---|---|
| Magnesite - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Magnesite - Respirable fraction. | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Aluminum oxide - Respirable fraction. | TWA | 1 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Aluminum oxide - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction. | TWA | 0.025 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable. | TWA | 2.4 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| | TWA | 0.1 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| Crystalline Silica (Quartz)/ Silica Sand - Total dust. | TWA | 0.3 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| Ammonium hydroxide | STEL | 35 ppm | US. ACGIH Threshold Limit Values (2011) |
| | TWA | 25 ppm | US. ACGIH Threshold Limit Values (2011) |
| | PEL | 50 ppm 35 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Talc - Respirable fraction. | TWA | 2 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| Talc | TWA | 20 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| Talc - Respirable. | TWA | 2.4 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| | TWA | 0.1 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| Talc - Total dust. | TWA | 0.3 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |



| Chemical name | type | Exposure Lin | nit Values | Source |
|---|-------|--------------|--------------|---|
| Calcium carbonate - Total dust. | STEL | | 20 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Calcium carbonate - Respirable fraction. | TWA | | 3 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Calcium carbonate - Total dust. | TWA | | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Calcium carbonate - Total dust. | TWA | | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| Titanium dioxide - Total dust. | TWA | | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Titanium dioxide - Respirable fraction. | TWA | | 3 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Titanium dioxide | TWAEV | | 10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Titanium dioxide - Total dust. | TWA | | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| Propylene glycol - Aerosol. | TWAEV | | 10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Propylene glycol - Vapor and aerosol, inhalable fraction. | TWAEV | 50 ppm | 155 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Zinc oxide - Respirable. | TWA | | 2 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | STEL | | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |



| Zinc oxide - Respirable fraction. | TWAEV | 2 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
|-----------------------------------|-------|----------|--|
| | STEL | 10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |



| Zinc oxide - Fume. | TWA | 5 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
|---|-------|----------------|---|
| Zinc oxide - Total dust. | TWA | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| Zinc oxide - Fume. | STEL | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| Cellulose - Respirable fraction. | TWA | 3 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Cellulose - Total dust. | TWA | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Cellulose | TWAEV | 10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Cellulose - Total dust. | TWA | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction. | TWA | 0.025 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable. | TWAEV | 0.10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable dust. | TWA | 0.1 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| Talc - Respirable. | TWA | 2 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Talc - Respirable particles. | TWAEV | 2 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Talc | TWAEV | 2 fibers/mL | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Talc - Respirable dust. | TWA | 3 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |



| Appropriate Engineering Controls | Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required. |
|-------------------------------------|--|
| Individual protection measures, | such as personal protective equipment |
| General information: | Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc. |
| Eye/face protection: | Wear safety glasses with side shields (or goggles). |
| Skin Protection Hand Protection: | Use suitable protective gloves if risk of skin contact. |
| Other: | Wear suitable protective clothing. |
| Respiratory Protection: | In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor. |
| Hygiene measures: | Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. |

9. Physical and chemical properties

Appearance

| Appearance | |
|--|---|
| Physical state: | liquid |
| Form: | liquid |
| Color: | Brown |
| Odor: | Mild |
| Odor threshold: | No data available. |
| pH: | 9 - 10 |
| Melting point/freezing point: | No data available. |
| Initial boiling point and boiling range: | No data available. |
| Flash Point: | No data available. |
| Evaporation rate: | Slower than Ether |
| Flammability (solid, gas): | No |
| Upper/lower limit on flammability or explosive | ve limits |
| Flammability limit - upper (%): | No data available. |
| Flammability limit - lower (%): | No data available. |
| Explosive limit - upper (%): | No data available. |
| Explosive limit - lower (%): | No data available. |
| Vapor pressure: | No data available. |
| Vapor density: | Vapors are heavier than air and may travel along the floor and in the bottom of containers. |
| Relative density: | 1.33 |
| Solubility(ies) | |
| | |



| Solubility in water: | Soluble |
|--|--------------------|
| Solubility (other): | No data available. |
| Partition coefficient (n-octanol/water): | No data available. |
| Auto-ignition temperature: | No data available. |
| Decomposition temperature: | No data available. |
| Viscosity: | No data available. |

10. Stability and reactivity

| Reactivity: | No data available. |
|--|---|
| Chemical Stability: | Material is stable under normal conditions. |
| Possibility of Hazardous Reactions: | No data available. |
| Conditions to Avoid: | Avoid heat or contamination. |
| Incompatible Materials: | Strong acids. Strong bases. |
| Hazardous Decomposition Products: | Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. |

11. Toxicological information

| Information on likely routes of exposure | | |
|--|---|--|
| Ingestion: | May be ingested by accident. Ingestion may cause irritation and malaise. | |
| Inhalation: | In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes. | |
| Skin Contact: | May be harmful in contact with skin. | |
| Eye contact: | Eye contact is possible and should be avoided. | |

Information on toxicological effects

| Acute toxicity (list all possible routes of exposure) |
|---|
|---|

| Oral Product: | No data available. |
|--------------------------|------------------------|
| Dermal Product: | ATEmix: 3,888.89 mg/kg |
| Inhalation Product: | ATEmix: 3.02 mg/l |
| Barrada da de construito | |

Repeated dose toxicity
Product:No data available.



Skin Corrosion/Irritation

Carcinogenicity Product: Version: 1.0 Revision Date: 08/17/2015

| Ρ | roduct: | No data available. |
|--|---|---|
| Serious Eye Damage/Eye Irritation Product: No data available. | | |
| S | pecified substance(s): Calcium carbonate | in vivo (Rabbit, 24 - 72 hrs): Not irritating |
| | Titanium dioxide | in vivo (Rabbit, 24 - 72 hrs): Not irritating |
| | Propylene glycol | (Human): Irritating |
| | Zinc oxide | in vivo (Rabbit, 24 - 72 hrs): Not irritating |
| | Magnesite | In vitro (Reconstituted Corneal Epithelium model, 10 min): Not irritating |
| | Aluminum oxide | in vivo (Rabbit, 24 hrs): Not irritating |
| | Ammonium hydroxide | Severely Irritating |
| Respiratory or Skin Sensitization Product: No data available. | | |

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No data available.

| Titanium dioxide | Overall evaluation: Possibly carcinogenic to humans. |
|--|--|
| Crystalline Silica (Quartz)/ Silica Sand | Overall evaluation: Carcinogenic to humans. |
| Talc | Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Possibly carcinogenic to humans. |

US. National Toxicology Program (NTP) Report on Carcinogens:

| Crystalline | Silica | Known To Be Human Carcinogen. |
|-------------|--------|-------------------------------|
| (Quartz)/ | Silica | - |
| Sand | | |

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified



Germ Cell Mutagenicity

| In vitro Product: | No data available. |
|--|--|
| In vivo Product: | No data available. |
| Reproductive toxicity Product: | No data available. |
| Specific Target Organ Toxicity - Product: | Single Exposure No data available. |
| Specific Target Organ Toxicity - Product: | |
| | No data available. |
| Aspiration Hazard Product: | No data available. No data available. |

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

| Fish Product: | No data available. |
|--|--|
| Specified substance(s): Calcium carbonate | LC 50 (Western mosquitofish (Gambusia affinis), 96 h): > 56,000 mg/l Mortality |
| Titanium dioxide | LC 50 (Mummichog (Fundulus heteroclitus), 96 h): > 1,000 mg/l Mortality |
| Propylene glycol | LC 50 (Fathead minnow (Pimephales promelas), 96 h): 55,770 mg/l Mortality |
| Zinc oxide | LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2,246 mg/l Mortality |
| Ammonium hydroxide | LC 50 (Western mosquitofish (Gambusia affinis), 96 h): 15 mg/l Mortality |
| Aquatic Invertebrates Product: | No data available. |
| Specified substance(s): Titanium dioxide | EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication |
| Propylene glycol | EC 50 (Water flea (Daphnia magna), 48 h): > 10,000 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): > 10,000 mg/l Intoxication |



| | LC 50 (Brine shrimp (Artemia salina), 24 h): > 10,000 mg/l Mortality |
|--------------------|---|
| Zinc oxide | LC 50 (Water flea (Daphnia magna), 48 h): 24.6 mg/l Mortality |
| Ammonium hydroxide | LC 50 (Water flea (Daphnia magna), 25 h): 60 mg/l Mortality LC 50 (Water flea (Ceriodaphnia dubia), 48 h): > 0 - 10 mg/l Mortality |

Chronic hazards to the aquatic environment:

| Fish Product: | No data available. |
|--|--|
| Specified substance(s): Titanium dioxide | LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result |
| Propylene glycol | NOAEL (Pimephales promelas, 7 d): 11,530 mg/l experimental result |
| Zinc oxide | NOAEL (Oncorhynchus mykiss, 30 d): 974 μ g/l interpreted |
| Aluminum oxide | NOAEL (Pimephales promelas, 28 d): 4.7 mg/l experimental result |
| Aquatic Invertebrates Product: | No data available. |
| Toxicity to Aquatic Plants Product: | No data available. |
| Persistence and Degradability | |
| Biodegradation Product: | No data available. |
| BOD/COD Ratio Product: | No data available. |
| Bioaccumulative Potential Bioconcentration Factor (BC Product: | F) No data available. |
| Partition Coefficient n-octan Product: | ol / water (log Kow) No data available. |
| Specified substance(s): Propylene glycol | Log Kow: -0.92 |
| Mobility in Soil: | No data available. |
| Other Adverse Effects: | No data available. |



13. Disposal considerations Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

| Chemical Identity | <u>OSHA hazard(s)</u> |
|-------------------|------------------------|
| Acrylonitrile | Liver |
| | Central nervous system |
| | Flammability |
| | Eye irritation |
| | Skin irritation |
| | Skin sensitization |
| | Respiratory irritation |
| | Cancer |
| | Acute toxicity |



CERCLA Hazardous Substance List (40 CFR 302.4):

| Chemical Identity | Reportable quantity |
|-------------------------|---------------------|
| Ammonium hydroxide | 1000 lbs. |
| n-(3,4-dichlorophenyl)- | 100 lbs. |
| n,n-dimethylurea | |
| Methyl benzimidazole-2- | 10 lbs. |
| yl carbamate | |
| Ammonia | 100 lbs. |
| Acrylamide | 5000 lbs. |
| Acrylonitrile | 100 lbs. |
| Barium sulfate | 1000 lbs. |

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

| | <u>Reportable</u> | |
|-------------------|-------------------|-----------------------------|
| Chemical Identity | <u>quantity</u> | Threshold Planning Quantity |
| Ammonia | 100 lbs. | 500 lbs. |
| Acrylamide | 5000 lbs. | |
| Acrylonitrile | 100 lbs. | 10000 lbs. |
| | | |

SARA 304 Emergency Release Notification

| Chemical Identity | Reportable quantity |
|-------------------------|---------------------|
| Zinc oxide | |
| Ammonium hydroxide | 1000 lbs. |
| n-(3,4-dichlorophenyl)- | 100 lbs. |
| n,n-dimethylurea | |
| Methyl benzimidazole-2- | 10 lbs. |
| yl carbamate | |
| Ammonia | 100 lbs. |
| Phthalocyanine green | |
| Acrylamide | 5000 lbs. |
| Acrylonitrile | 100 lbs. |
| Barium sulfate | 1000 lbs. |
| | |



SARA 311/312 Hazardous Chemical

| Chemical Identity | Threshold Planning Quantity |
|------------------------------|-----------------------------|
| Ammonia | 500lbs |
| Acrylamide | 500lbs |
| Acrylonitrile | 500lbs |
| Calcium carbonate | 500 lbs |
| Titanium dioxide | 500 lbs |
| Propylene glycol | 500 lbs |
| Zinc oxide | 500 lbs |
| Cellulose | 500 lbs |
| Clay | 500 lbs |
| Magnesite | 500 lbs |
| Aluminum oxide | 500 lbs |
| Crystalline Silica (Quartz)/ | 500 lbs |
| Silica Sand | |
| Ammonium hydroxide | 500 lbs |
| Talc | 500 lbs |
| | |

SARA 313 (TRI Reporting)

Chemical Identity

Zinc oxide

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

| Chemical Identity | Reportable quantity |
|-------------------|----------------------------|
| Ammonia | 10000 lbs |
| Ammonia | 20000 lbs |
| Acrylonitrile | 20000 lbs |

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity Calcium carbonate Titanium dioxide Propylene glycol Zinc oxide Cellulose

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium carbonate Titanium dioxide Zinc oxide Crystalline Silica (Quartz)/ Silica Sand Ammonia Acrylamide Acrylonitrile



Chemical Identity

Calcium carbonate Titanium dioxide Propylene glycol Zinc oxide Cellulose

US. Rhode Island RTK

<u>Chemical Identity</u> Zinc oxide

Other Regulations:

| Regulatory VOC (less water | 22 g/l |
|----------------------------|--------|
| and exempt solvent): | |
| VOC Method 310: | 0.91 % |

Inventory Status:

Australia AICS:

Canada DSL Inventory List:

EINECS, ELINCS or NLP:

Japan (ENCS) List:

China Inv. Existing Chemical Substances:

Korea Existing Chemicals Inv. (KECI):

Canada NDSL Inventory:

Philippines PICCS:

US TSCA Inventory:

New Zealand Inventory of Chemicals:

Japan ISHL Listing:

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.



Japan Pharmacopoeia Listing:

One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

| Revision Date: | 08/17/2015 |
|----------------------|---|
| Version #: | 1.0 |
| Further Information: | No data available. |
| Disclaimer: | For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. |