

Version: 1.0 Revision Date: 08/13/2015

SAFETY DATA SHEET

1. Identification

Material name: BRUSH GRADE MASTIC 5 GL Material: 360650 805

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Incorporated 3735 Green Road BEACHWOOD OH 44122 US

Contact person: Telephone: Emergency telephone number:

EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health	Hazards
--------	---------

Serious Eye Damage/Eye Irritation	Category 2A
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A

Acute toxicity, oral	29.24 %
Acute toxicity, dermal	29.24 %
Acute toxicity, inhalation, vapor	99.3 %
Acute toxicity, inhalation, dust or mist	100 %
Unknown toxicity - Environment	
Acute hazards to the aquatic	98.54 %
environment	

environment	
Chronic hazards to the aquatic	100 %
environment	

Label Elements

Hazard Symbol:



Signal Word:

Danger



Hazard Statement:	Causes serious eye irritation. May cause genetic defects. May cause cancer.
Precautionary Statement:	
Prevention:	Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*		
Asphalt	8052-42-4	40 - 70%		
Stoddard solvent (Mineral 8052-41-3 Spirits)		15 - 40%		
Cellulose	9004-34-6	7 - 13%		
Magnesium aluminum silicate	12174-11-7	3 - 7%		
Clay	1332-58-7	1 - 5%		
1,2,4-Trimethylbenzene	95-63-6	0.5 - 1.5%		
Nonane	111-84-2	0.5 - 1.5%		
Hydrodesulfurized middle distillate	64742-80-9	0.1 - 1%		
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1%		
Xylene	1330-20-7	0.1 - 1%		

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor//if you feel unwell. Rinse mouth.
Inhalation:	Move to fresh air.
Skin Contact:	Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.



Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.				
Most important symptoms/effect	Most important symptoms/effects, acute and delayed				
Symptoms:	May cause skin and eye irritation.				
Indication of immediate medical a	ttention and special treatment needed				
Treatment:	Symptoms may be delayed.				
5. Fire-fighting measures					
General Fire Hazards:	No unusual fire or explosion hazards noted.				
Suitable (and unsuitable) e	xtinguishing media				
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.				
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.				
Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.				
Special protective equipment an	d precautions for firefighters				
Special fire fighting procedures:	No data available.				
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.				
6. Accidental release measure	S				
Personal precautions, protective equipment and emergency procedures:	No data available.				
Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.				
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.				
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.				



7. Handling and storage

Precautions for safe handling:	Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities:	Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values		Source
Asphalt - Inhalable fraction as benzene solubles	TWA		0.5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	500 ppm	2,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Cellulose	TWA		10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Cellulose - Total dust.	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Cellulose - Respirable fraction.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Clay - Respirable fraction.	TWA		2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Clay - Total dust.	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
1,2,4-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values (2011)
Nonane	TWA	200 ppm		US. ACGIH Threshold Limit Values (02 2012)
Hydrodesulfurized middle distillate - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA		2.4 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)



			er cubic oot of air	
	TWA	0.1	l mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Crystalline Silica (Quartz)/ Silica Sand - Total dust.	TWA	0.3	3 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Xylene	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values	Source
Asphalt - Aerosol, inhalable as benzene solubles	TWA	0.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Asphalt - Inhalable fraction as benzene solubles	TWAEV	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Asphalt - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Stoddard solvent (Mineral Spirits)	STEL	580 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	290 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Stoddard solvent (Mineral Spirits)	TWAEV	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	525 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (1 2008)
Cellulose - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupationa Health and Safety Regulation 296/9 as amended) (07 2007)
Cellulose - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupationa Health and Safety Regulation 296/9 as amended) (07 2007)
Cellulose	TWAEV		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cellulose - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (1 2008)
Clay - Respirable.	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupationa Health and Safety Regulation 296/9 as amended) (07 2007)
Clay - Respirable fraction.	TWAEV		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Clay - Respirable dust.	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry or Labor - Regulation Respecting the Quality of the Work Environment) (7 2008)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupationa Health and Safety Regulation 296/9 as amended) (07 2007)
1,2,4-Trimethylbenzene	TWAEV	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12008)
Hydrodesulfurized middle distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupationa Health and Safety Regulation 296/9 as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational



				Health and Safety Regulation 296/97 as amended) (05 2013)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97 as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWAEV		0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0	.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97 as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97 as amended) (07 2007)
Xylene	TWAEV	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (1. 2008)
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (1: 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.



Individual protection measures, such as personal protective equipment

General information:	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes.

9. Physical and chemical properties

Appearance

••	
Physical state:	liquid
Form:	Viscous Liquid
Color:	Black
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	471 °C 880 °F
Flash Point:	No data available.
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or expl	osive limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	0.959
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.



Decomposition temperature:	No data available.
Viscosity:	No data available.
10. Stability and reactivity	
Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of Hazardous Reactions:	No data available.
Conditions to Avoid:	Avoid heat or contamination.
Incompatible Materials:	Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates).
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.
11. Toxicological information	

Information on likely routes of exposure

Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation.
Eye contact:	Causes serious eye irritation.

Information on toxicological effects

Acute toxicity (list all possible	routes of exposure)
-----------------------------------	---------------------

Oral Product:	No data available.
Dermal Product:	ATEmix: 2,461.54 mg/kg
Inhalation Product:	No data available.
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.



Serious Eve Damage/Eve Irritation

	Eye Damage/Eye Irritati roduct:	on No data available.
S	pecified substance(s): Asphalt	in vivo (Rabbit, 24 hrs): Not irritating
	Stoddard solvent (Mineral Spirits)	Irritating
	1,2,4-Trimethylbenzene	in vivo (Rabbit, 30 min): Not irritating
	Nonane	in vivo (Rabbit, 24 - 72 hrs): Not irritating
	Hydrodesulfurized middle distillate	in vivo (Rabbit, 24 hrs): Not irritating
	Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
-	itory or Skin Sensitizatio roduct:	n No data available.
	ogenicity roduct:	No data available.
IARC M	onographs on the Evalua	ation of Carcinogenic Risks to Humans:
	Asphalt	Overall evaluation: Possibly carcinogenic to humans.
	Magnesium aluminum silicate	Overall evaluation: Possibly carcinogenic to humans. Overall evaluation: Not classifiable as to carcinogenicity to humans.
	Hydrodesulfurized middle distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans. Overall evaluation: Not classifiable as to carcinogenicity to humans.
	Crystalline Silica (Quartz)/ Silica Sand	Overall evaluation: Carcinogenic to humans.
US. Nat	i onal Toxicology Progra Hydrodesulfurized	m (NTP) Report on Carcinogens: Known To Be Human Carcinogen.
	middle distillate	

- middle distillate Crystalline Silica Known To Be Human Carcinogen. (Quartz)/ Silica Sand
- US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified



Germ Cell Mutagenicity

In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	No data available.
Specific Target Organ Toxicity Product:	- Single Exposure No data available.
	No data available.
Product: Specific Target Organ Toxicity	No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:	No data available.	
Specified substance(s): 1,2,4-Trimethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l Mortality	
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality	
Aquatic Invertebrates Product:	No data available.	
Specified substance(s): 1,2,4-Trimethylbenzene	LC 50 (Scud (Elasmopus pectinicrus), 24 h): 4.89 - 5.62 mg/l Mortality	
Xylene	LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality	

Chronic hazards to the aquatic environment:

Fish Product:

No data available.

Specified substance(s):



Asphalt	NOAEL (Oncorhynchus mykiss, 28 d): >= 1,000 mg/l interpreted	
Nonane	NOAEL (Oncorhynchus mykiss, 28 d): 0.252 mg/l QSAR	
Hydrodesulfurized middle distillate	NOAEL (Oncorhynchus mykiss, 14 d): 0.069 mg/l QSAR	
Xylene	NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result	
Aquatic Invertebrates Product:	No data available.	
Toxicity to Aquatic Plants Product:	No data available.	
Persistence and Degradability		
Biodegradation Product:	No data available.	
BOD/COD Ratio Product:	No data available.	
Bioaccumulative Potential Bioconcentration Factor (BC Product:	F) No data available.	
Partition Coefficient n-octanol / water (log Kow) Product: No data available.		
Specified substance(s): Stoddard solvent (Mineral Spirits)	Log Kow: 3.16 - 7.15	
Nonane	Log Kow: 5.46	
Xylene	Log Kow: 3.12 - 3.20	
Mobility in Soil:	No data available.	
Other Adverse Effects:	No data available.	
13. Disposal considerations		
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.	
Contaminated Packaging:	No data available.	



14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Asphalt	100 lbs.
Nonane	100 lbs.
Xylene	100 lbs.
Naphthalene	100 lbs.
Ethylbenzene	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Asphalt	100 lbs.
Nonane	100 lbs.
Xylene	100 lbs.
Naphthalene	100 lbs.
Ethylbenzene	1000 lbs.



SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Asphalt	500 lbs
Stoddard solvent (Mineral	500 lbs
Spirits)	
Cellulose	500 lbs
Magnesium aluminum	500 lbs
silicate	
Clay	500 lbs
1,2,4-Trimethylbenzene	500 lbs
Nonane	500 lbs
Hydrodesulfurized middle	500 lbs
distillate	
Crystalline Silica (Quartz)/	500 lbs
Silica Sand	
Xylene	500 lbs
,	

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

<u>Chemical Identity</u> Asphalt Stoddard solvent (Mineral Spirits) Cellulose Clay

US. Massachusetts RTK - Substance List

<u>Chemical Identity</u> Asphalt Stoddard solvent (Mineral Spirits) Cellulose Clay Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

<u>Chemical Identity</u> Asphalt Stoddard solvent (Mineral Spirits) Cellulose Clay

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.



Other Regulations:

Regulatory VOC (less water and exempt solvent):	240 g/l	
VOC Method 310:	24.99 %	
Inventory Status: Australia AICS:		One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:		One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:		One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:		One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:		One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):		One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:		One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:		One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:		One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:		One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:		One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:		One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	08/13/2015
Version #:	1.0



Further Information:

Disclaimer:

No data available.

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.