

ECOmastic®

A Heavily Fibrated Asphalt Mastic for General Roof Repairs

Composition/Use: ECOMastic® is an asphalt-based, heavily fibrated mastic blended with penetrating oils and plasticizing agents. ECOMastic is asbestos free.

Basis Use: ECOMastic is used for repairing and restoring flashings and asphalt built-up roofing defects including blisters, cracks, and punctures. Added strength can be obtained by using reinforcing membranes.

Features:

- Sag resistant.
- Fibrated.
- Asbestos free.

Limitations: Not intended for use as a wet patching material. Not for use on coal tar membranes.

Packaging: ECOMastic is available in 18.9 and 208 litres (5 and 55 U.S. gallon) containers.

Grade: Trowel

APPLICATION DATA

Remove loose gravel, dirt, dust, deteriorated felt and foreign matter. Apply over clean, sound dry, base.

Coverage: Coverage rates will vary depending on ambient temperature and actual surface conditions.

Single coat: 3.3 L/m²
(12.5 ft.²/U.S. gal.).

1 ply BURmesh: 6.5 L/m²
(6.3 ft.²/U.S. gal.).

2 ply BURmesh: 9.7L/m²
(4.2 ft.²/U.S. gal.).

Precautions: Use ECOMastic with adequate ventilation. Users must read container labels and Material Safety Data Sheets for health and safety precautions prior to use.

Availability and Cost: Immediately available from Tremco Ltd. at strategic locations throughout Canada. Cost data is available from your local Tremco representative. For the name and telephone number of your local representative, call the Roofing Division in Toronto

at 416/421-3300 in Montreal at 514/521-9555 or 800/263-6046, or in the U.S. at 216/292-5000 or 800/852-6013.

Guarantee/Warranty: Tremco Inc. warrants ECOLastic to be free of defects and manufactured to meet published physical properties when cured and tested according to ASTM, CGSB and Tremco standards. Under this warranty, we will provide, at no charge, any ECOLastic product that is proved to be defective when applied in accordance to our written instructions and in applications recommended by Tremco as suitable for this product.

All claims concerning product defects must be made in writing within twelve (12) months of shipment. The absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product. This warranty is in lieu of any and all other warranties expressed or implied.

Maintenance: Written notice to Tremco within thirty (30) days is required after any alleged defect is noticed.

Technical Services: Your local Tremco Representative, in conjunction with the Tremco Engineering Service Department, provides problem analysis and assistance in developing recommendations for special applications. On-site instruction can generally be provided at a nominal charge. Their services are complemented and extended by the Tremco Research Center, which has earned a unique reputation in weatherproofing technology.

Statement of Policy and Responsibility: Tremco takes responsibility for the furnishing of quality materials and providing specifications and recommendations for their proper installation.

Tremco does not, either itself or its representatives, practice architecture or structural engineering. Tremco offers no opinion on, and

TREMCO
Roofing & Weatherproofing Peace of Mind™

expressly disclaims any responsibility for, the structural soundness of any roof deck on which its products may be applied. Opinions of competent structural engineers should be obtained by the owner as to the structural soundness of the roof deck, or its ability to properly support the contemplated roof installation. Tremco accepts no liability for any failure of the roof deck or resultant damages, and no Tremco Representative is authorized to vary this disclaimer.

TREMCO® 3735 Green Road
Beachwood, OH 44122
216-292-5000

An **RPM** Company

220 Wicksteed Ave
Toronto, ONT M4H 1G7
416-421-3300

100886E
Printed in USA

8/03