



# ROOFTOP SAFETY SOLUTIONS



## DYNAROUND RG™ (ROOF GUARD)

DynaRound RG™ Roof Guard ballasted rooftop guardrail system is designed for safety and fall protection on rooftop applications. Each system is made of durable, corrosion-resistant fiberglass reinforced plastic (FRP) composite uprights and non-FRP counterbalance weights and connector components. DynaRound RG provides the utmost in safety by protecting against injuries or death from accidental falls from the roof. This system meets all applicable safety standards in the U.S. and Canada to protect individuals on rooftop surfaces.



## DYNAROUND RG SLIMLINE™ (ROOF GUARD)

Fibergrate's ballasted rooftop guardrail system, DynaRound RG Slimline™, provides safety and fall protection on rooftop applications with fewer counterbalance bases than DynaRound RG. Similar to our DynaRound RG system, each Slimline system is made of durable, weather-resistant fiberglass reinforced plastic (FRP) composite uprights and rails, galvanized steel base weights, and galvanized connector components. This system meets applicable safety standards in the U.S. and Canada to protect people working at heights.



## DYNAROUND HATCH GUARD

DynaRound Hatch Guard provides a non-penetrating guard solution for safe entry and exit through roof access hatches. The adjustable self-closing gate prevents accidental entrance when hatch is open. The DynaRound Hatch Guard mounts directly to the roof hatch with a compression fit design so no drilling is necessary, which means the rooftop waterproofing system is not compromised.



## CORVEX® MOLDED GRATING WITH RUBBER FEET

Molded Walkway Grating is made with a unique Corvex resin system that outperforms many competitive fiberglass and metal products. Our molded grating is corrosion resistant, lightweight, slip resistant, and easy to install. Specially designed rubber feet can be added to molded grating, elevating it 1/2" above the surface, offering an economical raised walkway solution for use around maintenance equipment, machines, wet areas, and rooftop walkway areas.



## FRP DYNARAIL® SAFETY LADDERS

DynaRail® Safety Ladder Systems combine a corrosion resistant properties with a low maintenance design to ensure a long life cycle. Ladder rungs include heavily serrated flutes for slip resistant footholds that are easy on the hands while ensuring safety. Our system is designed and manufactured to be easily installed with no guesswork involved. Components are lightweight and easy to fabricate, which saves you on labor and equipment. UV inhibitors in the resin along with a secondary UV coating maximize protection from the effects of UV weathering. The DynaRail safety ladder system meets or exceeds all OSHA requirements.



## CROSSOVERS

Our FRP Crossovers are pre-engineered and both corrosion- and slip-resistant. Available in a variety of heights that address most standard clearances, these Crossovers provide a cost-effective, safe solution over many rooftop obstructions. Crossover systems create a safe working environment, are lightweight, easy to install and designed to meet all applicable safety standards in the U.S. and Canada.



## DYNAROUND SLIMLINE WARNING LINES

DynaRound Warning Lines are available in a heavy and light duty design. Our heavy-duty warning line systems can be used as a permanent warning system with heavy-duty galvanized base plates, plastic coated steel cable, and plastic pennants. The heavy-duty stanchions and bases are designed to withstand years of use. The standard system includes three stanchions, three bases, and 100' feet of plastic coated steel cable with flags. Our light-duty warning line system can be used as a temporary warning system. This system includes three folding stanchions and 100' of nylon flagged line. Both systems meet all applicable safety standards in the U.S. and Canada to protect individuals on rooftop surfaces.



## DYNAWEIGHT FALL PROTECTION SYSTEM

DynaWeight Fall Protection System is the perfect solution for fall protection when circumstances require non-penetrating versatility. This system is tested and approved for use on flat rooftop surfaces (single ply, BUR, concrete, modified bitumen membranes, liquid applied membranes- AlphaGuard™ BIO, AlphaGuard™ MT/MTS, and AlphaGuard™ PUMA), with a maximum incline of 5 degrees. It provides tie off options for two people if used for fall restraint or one person for fall arrest, sets up quickly and is easy to move. The DynaWeight Fall Protection System is corrosion resistant and meets all applicable safety standards in the U.S. and Canada to protect individuals on rooftop.

All Fibergrate Roof Top Safety Solutions are available exclusively through Tremco Roofing and Building Maintenance



Phone: 800-852-6013



www.tremcoroofing.com



SafetySolutions@tremcoinc.com

Fibergrate Composite Structures believes the information contained here to be true and accurate. Fibergrate makes no warranty, expressed or implied based on this literature and assumes no responsibility for consequential or incidental damages in the use of these products and systems described, including any warranty of merchantability or fitness. Information contained here is for evaluation only.