

# SOLARGARD® CLEAR COAT

#121005P - 5 gallon pail

## Acrylic sealer and top coat

### Description

SOLARGARD CLEAR COAT is a low odor, semi-gloss water based clear acrylic sealer and top coat. SOLARGARD CLEAR COAT is asbestos free.

### Uses

SOLARGARD CLEAR COAT is an exterior clear sealer which provides an attractive semi-gloss protective finish to acrylic roof coatings. SOLARGARD CLEAR COAT is especially recommended for use over freshly applied acrylic coatings which are tinted to deep shades in order to help in preserving the long term colorfast property of the base coating. In certain situations, SOLARGARD CLEAR COAT can restore the original color of an acrylic coating which has faded due to exposure to salts, airborne chemicals, and other environmental conditions.

### Limitations

Not intended to perform under ponded water conditions. Positive drainage is required. Not to be exposed to solvents, oils, or other chemicals or contaminants known to be harmful to acrylic coatings. Surfaces must be clean and free of dirt, dust, and other contaminants prior to application of SOLARGARD CLEAR COAT. Do not apply excessive amounts of SOLARGARD CLEAR COAT over deep colored acrylic coatings since heavy coverages and heavy overlapping material strokes may lead to a discoloration of the base color. Not recommended for rusted metal surfaces unless surface is first properly prepared, a corrosion resistant primer is applied, and an acrylic coating has been applied. Do not apply over silicone or Kynar (PVDF) coated substrates. Do not apply SOLARGARD CLEAR COAT below grade. Do not apply unless temperatures are at least 45°F and rising. Do not apply if temperatures are expected to drop below 45°F within 48 hours of application. Do not apply to wet surfaces. Do not apply unless the ambient and surface temperatures are at least 5°F above the dew point. Do not apply if rain is expected within 12 hours. If temperatures drop below 60°F, do not apply if rain is expected within 24 hours. Store containers at temperatures above 32°F. Do not allow containers to freeze. Store containers indoors in a heated area.

### Preparation

Surface must be clean, dry, and free from dust, oil, and other contaminants. Power wash surface if required to remove oil, grease, dirt, chalking, scale, rust, stains, and loose paint. When SOLARGARD CLEAR COAT is specified for application to an acrylic coating system, such as SOLARGARD HY-BUILD or SOLARGARD ELASTOMERIC 6083, refer to individual product data sheets for complete instructions.

### Application

Previously applied acrylic coatings must be touch dry and able to support foot traffic without tracking prior to application of SOLARGARD CLEAR COAT. Apply a single coat of SOLARGARD CLEAR COAT to a clean, dry surface by either short nap roller, brush, or spray. Do not apply excessive material or heavy overlapping material courses, especially when applying over deep color shades, since excessive coverages of SOLARGARD CLEAR COAT may adversely affect the final color of the base coating.

### Coverage

Application rates will vary depending on actual surface conditions, such as porosity and texture. For smooth, non-porous surfaces, apply SOLARGARD CLEAR COAT at a coverage rate of 300-400 sq. ft./gallon. For porous surfaces, apply SOLARGARD CLEAR COAT at a coverage rate of 200 sq. ft./gallon.

Additional material may be required for coverage of corrugated roof panels depending on rib size, height and degree of surface porosity.

### Equipment Recommendation

**Airless Spray:** Pneumatic, hydraulic, or electric pump with a minimum 1,800 psi material output pressure. Reversible spray tip with a 0.013" to 0.019" orifice and a 40 to 60 degree spray fan. Material spray lines must be properly rated for the maximum working pressure of the pump being used.

**Roller:** Short to medium nap

**Brush:** China bristle, nylon/polyester, or nylon

### Maintenance

It is recommended that the coating application be checked on a regular schedule with additional inspections after the system has been exposed to severe conditions. Recoating or small area touch up can be made at any time by following recommended application procedures.

### Technical Services

Technical advice or service on suitability of material for specific application and end-use requirements is available from the manufacturer. Refer to label and Safety Data Sheet (SDS) for precautionary information.

## TECHNICAL DATA

<b>Grade</b>	<b>Brush/roll/spray</b>
<b>Color</b>	<b>Clear</b>
<b>Thinning</b>	<b>Do not thin</b>
<b>Clean Up</b>	<b>Water</b>
<b>Storage Life</b>	<b>One year in unopened containers</b>



**REPUBLIC**  
RESTORATION SYSTEMS

**TREMCO**

# SOLARGARD® CLEAR COAT

---



**Tremco Incorporated**  
3735 Green Road, Beachwood, OH 44122  
U.S.: 800-551-7081  
50 Beth Neelson Drive, Toronto, Ontario M4H 1M6  
CA: 800-668-9879  
[www.tremcoroofing.com](http://www.tremcoroofing.com)

---

SOLARGARD is a U.S. registered trademark of Republic Powdered Metals, Inc.

The information provided on this data sheet is effective as of May 2016 and supersedes all previous data concerning this product and its application.

© Republic Restoration Systems by Tremco, 2016. All Rights Reserved.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.