Tremco TPA Single Ply Roofing Systems Prefabricated Universal Corners

DESCRIPTION BASIC USES

TPA unreinforced membrane

The Tremco TPA prefabricated corners must be used for sealing the corners of all pitch pans, curbs, and walls. They are uniform in shape and size and provide water tightness at corners formed by TPA coated metal and flashing membrane.

SIZE

APPLICATION

3 1/2" (nominal) to all edges

Installation Procedures:

- 1. The corners shall be cut at the scored lines to form either an inside or outside corner.
- **2.** Use proper heat welding techniques to fully weld the corner to the flashing following published Tremco specifications and details.
- 3. Universal Corners can only be installed by hot-air heat-welding.

MAINTENANCE

TECHNICAL SUPPORT

PRECAUTIONS

Your local Tremco Roofing Sales Representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

Your local Tremco Roofing Sales Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.

TREMCO

Roofing & Building Maintenance www.tremcoroofing.com 3735 Green Road Beachwood, Ohio 44122 1.800.852.6<u>013</u>_____

220 Wicksteed Avenue Toronto, Ontario, M4H 1G7 1.800.668.9879 Tremco Roofing and Building Maintenance is part of Tremco Construction Products Group. Tremco is a US Registered trademark of Tremco CPG Inc.

The information provided on this data page supersedes all previous data concerning this product and its application. The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Terreco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S OPTION, TO THE REPLACEMENT OF GODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.