

# TREMPrime™ QD Low Odor

## A Quick-Drying Low Odor Primer For Asphalt Roofs

**Composition:** TREMprime™ QD Low Odor is formulated from refined select asphalt to produce an effective priming base for the application of Tremco Roofing Systems. TREMprime QD Low Odor is asbestos free.

**Basic Uses:** TREMprime QD Low Odor promotes adhesion between weathered surfaces and Tremco coatings, adhesives, and maintenance systems. TREMprime QD Low Odor is also used as a metal primer to enhance the adhesion of asphalt cements and flashing adhesives.

**Limitations:** TREMprime QD Low Odor is not intended to be used as a final coating.

Not intended for use over Kynar or other PVDF resin coatings.

Do not apply when rain appears imminent.

Do not use with Tremco FAS-N-FREE® solvent free insulation adhesive.

Surfaces primed with TREMprime QD Low Odor must be reprimed if allowed to remain open for more than 24 hours.

PRODUCT ADVANTAGES	
Features	Benefits
Non-fibrated	• Allows maximum penetration of dried felts and porous substrates
Low Odor	• Minimizes disruption to building occupants.
Quick drying formula	• Minimizes wait for curing
Readily workable consistency	• Easily brushes into rougher substrates providing more uniform surfaces
Multi-purpose	• Can be used on metal work and other surfaces

**Grade:** Brush/Roll/Spray.

**Recommended spray equipment:** Minimum 11:1 ratio pump with 0.015" to 0.021" spray tip.

**Packaging:** TREMprime QD Low Odor is available in 5 and 55 gallon containers.

**Storage Life:** One year.

**Application:** Remove all loose dust, dirt, rotted felt, and foreign matter. Surface must be clean and dry.

When spraying TREMprime QD Low Odor take necessary precautions to prevent over-spray.

**Coverage:** Coverage will vary depending upon actual surface and application conditions. Approximately 200-400 ft<sup>2</sup>/gal(4.9-9.8 m<sup>2</sup>/L).

**Clean-Up:** Mineral Spirits.

**Precautions:** Use TREMprime QD Low Odor with adequate ventilation. Users must read container labels and Material Safety Data Sheets for health and safety precautions prior to use.

**Availability and Cost:** Contact your local Tremco Representative for pricing and availability. For the name and number of your representative call the Roofing Division at 216/292-5000.

**Maintenance:** Your local Tremco Roofing Representative can provide you with effective maintenance procedures which may

**TREMCO**

Roofing & Weatherproofing Peace of Mind™

vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

**Guarantee/Warranty:** Tremco Inc. warrants TREMprime QD Low Odor to be free of defects and to meet published physical properties when tested according to ASTM and Tremco standards. Under this warranty, any TREMprime QD Low Odor product that is proven to be defective when applied in accordance to our written instructions, and in applications recommended by Tremco as suitable for this product, will be replaced with like product at no charge. THIS IS BUYERS SOLE AND EXCLUSIVE REMEDY.

All claims concerning product defects must be made in writing within twelve (12) months of shipment. The absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product.

This warranty shall be IN LIEU OF any other warranty, express or implied, including but not limited to, any implied warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

**Technical Services:** Your local Tremco Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications. The services of the Tremco Research Center, which has earned a unique reputation in weatherproofing technology, complement and extend the services of the Tremco Technical Service Staff.

**Statement of Policy and Responsibility:** Tremco takes responsibility for furnishing quality materials and for providing specifications and recommendations for their proper installation.

As neither Tremco itself nor its Representatives practice architecture or engineering, Tremco offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure or its ability to

Physical/Performance Characteristics		
TREMprime QD™ Low Odor		
Property	Typical Value	Test Method
Asbestos content	None	ASTM D 276-87
Density @ 77°F (25°C)	7.8 lb/gal (934.8 kg/m <sup>3</sup> )	ASTM D 1475-90
Non-Volatile Content	52%	ASTM D 1644-88 (1981)
Flash point	>100°F	ASTM D 3278-82
Odor	Faint/Slight petroleum	
Vapor density	4.9-Mineral Spirits	

support a planned installation properly, the Owner should obtain the opinion of competent structural engineers before proceeding. Tremco accepts no liability for any structural failure or for resultant damages, and no Tremco Representative is authorized to vary this disclaimer.



3735 Green Road  
Beachwood, OH 44122  
216-292-5000

220 Wicksteed Ave  
Toronto, ONT M4H 1G7  
416-421-3300