

# TremFlash (TF) Tape

## A flexible, non-drying, gasket forming, sealant tape

**Composition:** TremFlash (TF)Tape is a flexible, butyl based sealant tape used to provide a compressible gasket when applied to surfaces to be joined by mechanical attachment.

**Basic Use:** TremFlash Tape is applied to metal termination bars and Elastomeric Flashing Membrane before attachment to vertical surfaces in flashing applications. The TremFlash Tape compresses when the materials are mechanically attached and helps to form a gasket seal between the components, especially where the substrate may be slightly uneven.

**Limitations:**

- Do not use on horizontal joints.
- Do not expose to standing water.
- Do not expose to constant contact with harsh chemicals such as acids, alkalis and organic solvents.

**Packaging:**

TremFlash Tape is available in 3 mm X 25 mm X 15.2 m (1/8" X 1" X 50') rolls and is packaged in cartons of 12 rolls. TremFlash Tape is conveniently applied to release paper backer to ease application and to prevent sticking to itself.

**Color:** TremFlash Tape is available in gray only.

**Storage Life:** Up to 1 year.

**Application:**

Apply the TremFlash Tape to the clean mating surface of the material to which is to be attached. Apply the TremFlash Tape by adhering the tape to the surface and unrolling the TremFlash Tape with the release paper intact. Put slight pressure on the backer during application to assure adhesion to the surface.

Remove the release paper backer. Assure that the TremFlash Tape remains clean when exposed. Apply the material to be attached to the clean, dry substrate. Mechanically attach the material slightly compressing the TremFlash Tape to form a gasket seal without over compressing the gasket.

The joint created between the attached material and the substrate may be caulked with either TremSeal D, TremSeal HP or Reglet Joint Sealant per Tremco application specifications.

**Cleaning:** Immediately remove excess TremFlash Tape from any surface with Tremply Solvent or Xylene as work progresses.

**Precautions:** Users must read container labels and Material Safety Date Sheets for health and safety precautions prior to use.

**Availability and Cost:** Contact your local Tremco Roofing Representative for pricing and availability. For the name and number of your Representative, call the Roofing Division at 216/292-5000.

**Maintenance:** Your local Tremco Roofing Representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

**Guarantee/Warranty:** Tremco Inc. warrants TremFlash Tape to be free of defects and to meet published physical properties when tested according to ASTM and Tremco standards. Under this warranty, any TremFlash Tape product that is proved to be defective when applied in accordance to our written instructions, and in applications recommended by Tremco as suitable for this product will be replaced with like product at no charge. THIS IS BUYERS SOLE AND EXCLUSIVE REMEDY.

All claims concerning product defects must be made in writing within twelve (12) months of shipment. The absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product.

**TREMCO**

Roofing & Weatherproofing Peace of Mind™

This warranty shall be IN LIEU OF any other warranty, express or implied, including but not limited to, any implied warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

**Technical Services:** Your local Tremco Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications. The services of the Tremco Research Center, which has earned a unique reputation in weatherproofing technology, complement and extend the services of the Tremco Technical Service staff.

**Statement of Policy and Responsibility:** Tremco takes responsibility for furnishing quality materials and for providing specifications and recommendations for their proper installation.

As neither Tremco itself nor its Representatives practice architecture or engineering, Tremco offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure or its ability to support a planned installation properly, the Owner should obtain the opinion of competent structural engineers before proceeding. Tremco accepts no liability for any structural failure or for resultant damages, and no Tremco Representative is authorized to vary this disclaimer.



3735 Green Road  
Beachwood, OH 44122  
216-292-5000

220 Wicksteed Ave  
Toronto, ONT M4H 1G7  
416-421-3300