

TremPly® TPO Bonding Adhesive LV3



An Accessory Designed for TremPly TPO Single Ply Roof System

FEATURES

- Low VOC (<250 g/l)
- Roller or brush applied
- Approximately 3 square coverage in a 5 gallon can.

BENEFITS

Low odor application, environmentally friendly

Ease of application

Extended square ft. coverage

DESCRIPTION:

TremPly® TPO Bonding Adhesive LV3 is a contact-type bonding adhesive specially designed for bonding TPO single-ply roofing membranes and flashings to various roofing substrates.

BASIC USES:

TremPly® TPO Bonding Adhesive LV3 contains less than 250 grams per liter of Volatile Organic Compounds (VOCs) and has been formulated using a blend of VOC-exempt and non-exempt solvents to be in compliance with air-quality regulations for single-ply roofing adhesives.

COLORS:

Amber

PACKAGING:

5-gallon pails (18.925-liter 38 pails) Weight, 38 lbs (17.24 kg.) per pail; 45 pails per pallet

PHYSICAL PROPERTIES:

Base: Synthetic polymer
Solvent: VOC-compliant blend
Flash point: 30.2°F (-1°C)
Viscosity: Nominal 2,750 cps
Coverage: 50-60 sq. ft./gallon (1.23 - 1.47 m²/liter)
Total Solids: 25% +/- 1%
Voc: <250 g/l
Shelf Life: 1 year, unopened
Open Time: Up to 60 minutes
Dry Time: 15- 25 minutes, depending on weather conditions
Application: Roller, brush, or spray
Storage: Recommended storage temperature is between 60°F - 80°F. Storage for continued periods outside this temperature range may shorten shelf life.
Installation Temperature: 40°F (4°C) and rising

MAINTENANCE:

Your local Tremco Roofing representative can provide you with effective maintenance procedures, which may vary depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

TECHNICAL SERVICES:

Your local Tremco Roofing representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



7163
3/20/18

www.tremcoroofing.com
 3735 Green Road
 Beachwood, Ohio 44122
 1.800.852.6013



50 Beth Neelson Drive
 Toronto, Ontario M4H 1M6
 1.800.668.9879

TremPly is a U.S. registered trademark of Tremco Incorporated.

The information provided on this data sheet is effective as of December 2017 and supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.