

Tremco Water Block Sealant



A high performance, low VOC, permanently flexible gun grade mastic that adheres to all approved substrates.

FEATURES

Low VOC formula (<150g/L)

Excellent adhesion to clean and dry substrates. No primer required

Excellent gunnability at low temperatures

Water resistant, even under immersion conditions

Non-skinning and non-curing

BENEFITS

Suitable for use in VOC regulated markets

Adheres to concrete, masonry, gypsum, metal, glass, plastic and wood surfaces

Wide application temperature range

Long term moisture barrier

Permanently flexible even at low temperatures

DESCRIPTION:

Tremco Water Block Sealant is a gray colored, high performance, low VOC, non-curing, permanently flexible gun grade Sealant. It maintains a positive seal by remaining flexible and adhered to all approved substrates.

BASIC USES:

Tremco Water Block Sealant is a non-curing, non-skinning secondary sealant designed for unexposed waterproofing applications. Tremco Water Block Sealant can be used:

- Behind termination bar
- Under roof drains
- Acoustical sealant
- Roof panel rib sealant
- Vapor barrier sealant

PACKAGING AND COVERAGE:

Tremco Water Block Sealant is available in the following package:

Pail Size	Packaging
10.3 fl. oz. (300 mL)	CT-0304-GR 30

Coverage rate will be approximately 10-12 lineal feet (3.0 - 3.7m) for a 1/2" (1.3cm) bead.

SURFACE PREPARATION:

All work surfaces should be clean, dry, free of dirt, dust, debris, oils, unadhered coatings, deteriorated membrane and other contaminants that may result in a surface that is not sound or is uneven. If necessary, clean the surface to receive the Tremco Water Block Sealant with an approved surface cleaner.

SAFETY:

Prior to working with this or any adhesive product consult product label and Safety Data Sheet (SDS) for necessary health and safety precautions.

APPLICATION:

1. Cut nozzle on cartridge to allow proper bead installation.
2. Apply an approximately 1/2" (1.3cm) size bead (or appropriate size bead to completely seal void) of Tremco Water Block Sealant between the objects to be sealed.
3. Install product and fasten accordingly. Note: Tremco Water Block Sealant is not intended to be used as a structural sealant or to replace mechanical fastening. It is intended for waterproofing only.
4. For drain applications, install a continuous bead of Tremco Water Block Sealant in between roof membrane and drain bowl. Install drain clamping ring according to drain manufacturers recommendations.

Tremco Water Block Sealant

APPLICATION: (continued)

5. Note: This is a non-skinning, non-curing sealant and is intended for unexposed applications only. Use Mineral Spirits or VM&P naphtha.

LIMITATIONS:

- Talc, dust, oil, ice, snow, or wet conditions inhibit good adhesion. Clean and dry surfaces are necessary for proper installation of this product.
- Not recommended for direct contact with insulating glass sealants.
- Not to be used in locations exposed to direct UV light.
- Not to be painted.
- Use only in unexposed areas.

PHYSICAL PROPERTIES:

Property	Results	Test Method
Base Polymer	Synthetic Rubber	FTIR
Adhesion	Excellent to most clean, dry surfaces	ASTM C 794
Water Resistance	No adhesion loss, no shrinkage, no chalking	
Flash Point	105°F (40°C)	ASTM D 56
VOC Content	<150 g/L	ASTM D 3960
Solids Content	85% Minimum	ASTM C 681
Weight/Gal	10.5 lbs.	ASTM D 1475
Application Properties		
Service Temperature	-40°F to 200°F (-40°C to 93°C)	ASTM D 3359
Application Temp.	20°F to 120°F (-6°C to 49°C)	ASTM C 603

NOTE: The foregoing information is published as general information only. The listed properties and performance characteristics are typical values and are not to be interpreted as manufacturing specifications.

CAUTION: All statements and technical information in this document are based on tests or data that Tremco believes is reliable. However, Tremco does not warrant or guarantee the accuracy or completeness of this information. The user has sole knowledge and control of factors that can affect the performance of Tremco's products in the user's intended application. It is the user's responsibility to conduct tests to determine the compatibility of Tremco's product with the design, structure, and materials of the user's end product and the suitability of Tremco's product for the user's method of application and intended use. The user assumes all risk and liability arising out of such use.



7048
09/27/16

www.tremcoroofing.com
3735 Green Road
Beachwood, Ohio 44122
1.800.852.6013



50 Beth Neelson Drive
Toronto, Ontario M4H 1M6
1.800.668.9879

Tremco Water Block Sealant is a U.S. registered trademark of Tremco, Inc.

The information provided on this data sheet is effective as of April 2016 and supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.