

SHEET-METAL EXPANSION JOINT
COVER WITH T-TYPE CLEAT

FLEXIBLE WEATHERPROOF
MEMBRANE CLOSURE

FLEXIBLE LINER TO SERVE AS
INSULATION RETAINER
(ATTACHED TO TOP OF CURB)

TOP OF CURB TO
DRAIN TO ONE SIDE

8" MINIMUM
FLASHING HEIGHT
ON LOW SIDE

COMPRESSIBLE
INSULATION

2 x 6 MIN. WOOD NAILER
ATTACHED TO SUBSTRATE—
OVERALL THICKNESS TO
MATCH INSULATION

SLOPE

PREMANUFACTURED
EXPANSION JOINT
COVER

OPTION

LIQUID APPLIED TOP COAT

LIQUID APPLIED BASE COAT

THREE-COURSE OVER ALL
MEMBRANE AND FLASHING LAPS

EXISTING ROOF MEMBRANE
AND FLASHINGS

EXISTING INSULATION

NOTES

1. PRIMING OF THE SUBSTRATE MAY BE REQUIRED, FOLLOW SPECIFICATIONS AND MANUFACTURER RECOMMENDATIONS.
2. FLASHING REQUIREMENTS ARE TYPICAL FOR BOTH SIDES OF THE EXPANSION JOINT.



SHEET TITLE:

BASE FLASHING AT EXPANSION JOINT
WITH METAL COVER PARTIALLY
REINFORCED RESTORATION

SCALE:

NTS

DRAWING No.:

DWG NO. LA-PR-08