

SHEET-METAL EXPANSION JOINT COVER WITH T-TYPE CLEAT

FLEXIBLE WEATHERPROOF MEMBRANE CLOSURE

FLEXIBLE LINER TO SERVE AS INSULATION RETAINER (ATTACHED TO TOP OF CURB)

TOP OF CURB TO DRAIN TO ONE SIDE

8" MINIMUM FLASHING HEIGHT ON LOW SIDE

COMPRESSIBLE INSULATION

2 x 6 MIN. WOOD NAILER ATTACHED TO SUBSTRATE—OVERALL THICKNESS TO MATCH INSULATION

PREMANUFACTURED EXPANSION JOINT COVER

OPTION

SLOPE

LIQUID APPLIED TOP COAT

LIQUID APPLIED REINFORCED BASE COAT

NEW BASE PLY INSTALLED ACCORDING TO SPECIFICATIONS

OPTIONAL FLASHING BASE PLY, CANT MAY BE REQUIRED

NEW INSULATION AND COVERBOARD

## NOTES

1. PRIMING OF THE SUBSTRATE MAY BE REQUIRED, FOLLOW SPECIFICATIONS AND MANUFACTURER RECOMMENDATIONS.
2. REINFORCEMENT MUST BE FULLY SATURATED OR ENCAPSULATED IN BASE COAT AS DESCRIBED IN SPECIFICATIONS.
3. FLASHING REQUIREMENTS ARE TYPICAL FOR BOTH SIDES OF THE EXPANSION JOINT.



SHEET TITLE:

BASE FLASHING AT EXPANSION JOINT WITH METAL COVER LIQUID APPLIED PLUS SYSTEM

SCALE:

NTS

DRAWING No.:

DWG NO. LA-PR-08