



## NOTES

1. WITH THE EXCEPTION OF THE TRANSITIONAL BAR DIVIDING THE FULLY ADHERED AREA FROM THE MECHANICALLY ATTACHED AREA, ALL ATTACHMENT MUST BE INSTALLED PERPENDICULAR TO THE METAL DECK FLUTE ORIENTATION.
2. PERIMETER AND CORNER WIDTH DIMENSIONS ARE DETERMINED BASED ON THE LESSER PRODUCT DERIVED BY MULTIPLYING THE BUILDING HEIGHT BY .4 (40%) OR THE LESSER BUILDING DIMENSION BY .1 (10%).
3. SPACING BETWEEN ROWS OF SECUREMENT IS REDUCED BY THE FOLLOWING FACTORS:  
PERIMETER - 60% OF THE PANEL WIDTH INSTALLED IN THE FIELD OF THE ROOF, SINCE NOBODY MANUFACTURES A 60% SHEET, HALF SHEETS ARE TYPICALLY USED.  
CORNER - 40% OF THE PANEL WIDTH INSTALLED IN THE FIELD OF THE ROOF.



SHEET TITLE:  
 CLASS 1-90 M/A INSULATION AND  
 ADHERED FIELD MEMBRANE - WITH M/A  
 MEMBRANE IN PERIMETER AND CORNERS

SCALE:  
 NTS

DRAWING No.:  
 DWG NO. 13