



PERIMETER AND CORNER WIDTH DIMENSIONS ARE DETERMINED BASED ON THE LESSER PRODUCT DERIVED BY MULTIPLYING THE BUILDING HEIGHT BY .4 (40%) OR THE LESSER BUILDING DIMENSION BY .1 (10%).

TREMCO APPROVED INSULATION INSTALLED IN THE FIELD OF THE ROOF IS SECURED IN ACCORDANCE WITH THE APPLICABLE CODE RATING REQUIREMENTS AND ENHANCED IN THE PERIMETER AND CORNER AREAS OF THE ROOF BY THE FOLLOWING FACTORS:
PERIMETER - 50% INCREASE OVER THE FIELD SECUREMENT RATE
CORNER - 100% INCREASE OVER THE FIELD SECUREMENT RATE

NOTES

1. REFER TO DETAILS FOR TYPICAL INDUCTION WELD ATTACHMENT METHODS. WHEN INSTALLING MULTIPLE LAYERS OF INSULATION, ALL END JOINTS SHALL BESTAGGERED



SHEET TITLE:
 INDUCTION WELD FIELD,
 PERIMETER & CORNER
 ATTACHMENT DESIGNATIONS

SCALE:
 NTS
 DRAWING No.:
 DWG NO. 58