Available Through



Part of Tremco Construction Products Group





SIMPLE INGENUITY

LEVEL.IT ADJUSTABLE PEDESTALS

- Simple, extended height range pedestal
- Patented design features exclusive internal coupler
- Durable commercial quality
- Fast and easy installation promotes labor savings
- Screw-to-adjust pedestals ensure perfectly level decks
- Impervious to water, mold, and freeze/thaw cycles
- Long lasting solution with no maintenance over time
- Made in the U.S.A.



©2013-2023 United Construction Products, Inc. All Rights Reserved. Covered by one or more patents or pending patents.

Tremco | 3735 Green Rd, Beachwood OH 44122 USA | 220 Wicksteed Ave, Toronto ON M4H 1G7 CAN | bisonip.com

April 2023

SPECIFICATIONS

- Supports 750 lbs (340 kg) FoS:3 per pedestal
 Select 1/8 or 3/16 inch (3.2 or 4.5 mm) tab size for pedestals
 Level.lt adjustable system height range is 2 to 12 inches (51 to 305 mm)
 Accessories available for heights from 1/8 to 2 inches (3.2 to 51 mm)
 Pedestals made of high density copolymer polypropylene
 Contains 20% post-industrial recycled material
 Impervious to water, mold, and freeze/thaw cycles
 Made in the U S A

- Made in the U.S.A.

		Model No.	Description	Height Range	Notes
Pedestals		LC-18 LC-316	Adjustable Pedestal	2" to 4-3/4" (51 to 121 mm)	
		C1	Coupler	Adds up to 1-1/2" (38 mm)	
		C4	Coupler	Adds up to 4" (102 mm)	
Tabs		LT18 LT316	Spacer Tab		Select 1/8" (3.2 mm) or 3/16" (4.5 mm) Tab Width
Accessories	B	VT18 VT316	Ultra Low Height Pedestal	1/8" (3.2 mm)	
		HD25-18 HD25-316 HD50-18 HD50-316 HD75-18 HD75-316	Fixed Height Stackable Pedestal	1/4" (6 mm) 1/2" (13 mm) 3/4" (19 mm)	Stack up to 4 Supports 1250 lbs (567 kg) FoS:3 per Pedestal
		LO-18 LO-316	Low Height Adjustable Pedestal	1-1/4" to 2" (32 to 51 mm)	
		B11	Flexible Shim	1/16" (1.5 mm)	
		PS1	Rigid Shim	1/8" (3.2 mm)	
		LD4	Base Leveler	Adds 1/4" (6 mm)	Stack up to 4 total to base of Pedestals For 1/4" per foot (2%) slope compensation each
	Ø.	FS-1	Wood Tile Fastening Kit		able Pedestals with long screw, ight Pedestals with short screw
	À	FS-12 FS-12-WT	12" Fastening Spline 3/16" (4.5 mm) Tab	Fastens Wood Tiles or Paver Trays to Adjustable Pedestals with long screw, and HD50 or HD75 Fixed Height Pedestals with short screw	
		JT	Joist Top Attachment	Adds 3/16" (4.5 mm)	Works with 2 x and 4 x lumber on Adjustable Pedestals
		FIB	Floating Insulation Base	12" x 12" x 11/16" (305 x 305 x 17 mm) For use over roofing systems with 20 to 40 psi insulation	
		FFB	Floating Foundation Base	12" x 12" x 1/4" (305 x 305 x 6 mm) For use over soil	
	/4" 3/4" Model HD75	1.1/4" to 2" Model LO 2" to 4.3/4 Model LC:	Top, Base, Yellow Coupler	4-3/4" to 6-1/4" Model LC	Base Leveler
prop	per use and installati	evel.It product specifications t on. Find specifications at www	to ensure w.bisonip.com.	+ C1 Coupler Model LC + C4 Coupler	8-3/4" to 12" Model LC + 2x C4 Couplers

Tremco | 3735 Green Rd, Beachwood OH 44122 USA | 220 Wicksteed Ave, Toronto ON M4H 1G7 CAN | bisonip.com