

AlphaGuard™ FC Catalyst

Powder reactive catalyst

DESCRIPTION

AlphaGuard FC Catalyst is a low odor, powder reactive agent used to catalyze AlphaGuard FC and PUMA liquid products.

BASIC USES

AlphaGuard FC Catalyst is mixed with AlphaGuard FC and PUMA liquid products to initiate the curing process.

PACKAGING

55 lbs (25 kg) bag packaged in a box container
50 - 100g bags (11 lbs/5 kg total) packaged in a box container

COLOR

White

GRADE

Powder

POT LIFE

10 - 15 minutes. **Pot life dependent on ambient, substrate, and product temperature temperature and the amount of AlphaGuard FC Catalyst used.*

STORAGE LIFE

12 months shelf life in unopened containers when properly stored.

Recommended storage is indoors in a ventilated, dry area removed from heat, open flame, ignition sources and direct sunlight. Storage temperatures should range from 60-70°F (15-21°C) and must not drop below 32°F (0°C) or exceed 110°F (43°C).

On the job site, materials should remain on the pallet until use and be stored in a shaded, ventilated area. Materials should be covered with a light-colored, reflective tarp for protection against the elements. Allow for adequate air flow inside the pallets.

Shelf life could be affected if the product is not stored properly.

APPLICATION

Usage: AlphaGuard FC Catalyst is used in a range of 1-6% of the weight of the AlphaGuard FC or PUMA liquid product selected. The amount of AlphaGuard FC Catalyst required is based on the type and amount of liquid product used as well as the ambient temperature.

Mixing: Use a heavy duty power drill with Jiffy Mixer attachment. Cordless drills are not recommended and may not properly mix the materials.

Mix the AlphaGuard FC or PUMA liquid product to achieve a uniform distribution and appearance of the product. Once properly mixed, AlphaGuard FC or PUMA liquid products can be poured off in smaller quantities into a second container. Add the appropriate amount of AlphaGuard FC Catalyst to the selected amount of liquid product and mix thoroughly for a minimum of two minutes until powder catalyst is completely dissolved. Catalyze only the amount of liquid product intended to be used within the expected pot life. The amount of AlphaGuard FC Catalyst required is based on the type and amount of liquid product used as well as the ambient temperature. Refer to mixing charts located on individual product data sheets for specific recommendations and requirements.

AlphaGuard™ FC Catalyst

MAINTENANCE

Your local Tremco Roofing representative can provide you with effective maintenance procedures, which may vary depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

TECHNICAL SUPPORT

Your local Tremco Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications. The services of the Tremco Research Center, which has earned a unique reputation in weatherproofing technology, complement and extend the service of the Tremco Service Staff.



Roofing & Building Maintenance

www.tremcoroofing.com

3735 Green Road
Beachwood, Ohio 44122
1.800.852.6013

220 Wicksteed Avenue
Toronto, Ontario, M4H 1G7
1.800.668.9879

Tremco Roofing and Building
Maintenance is part of Tremco
Construction Products Group.

Tremco is a US Registered trademark of Tremco CPG Inc.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.