

# TREMprime WB

## A Quick-Drying Water Based Asphaltic Primer

### FEATURES

Non-fibrated  
Adhesion promoters  
Quick drying formula  
Readily workable consistency  
Water based

### BENEFITS

- Allows maximum penetration of dried felts and porous substrates
- Conditions asphalts and felts to provide highly receptive surface for protection treatments
- Minimizes wait for curing
- Easily brushes into consistency rougher substrates providing more uniform surfaces
- Can be used on metalwork and other surfaces
- Environmentally cleaner
- Meets VOC standards

### DESCRIPTION

TREMprime WB is a water based polymer modified asphalt primer formulated from refined select asphalt, special adhesion, promoters and synthetic polymers which conditions a variety of roofing substrates prior to the application of Tremco Roofing Systems and coatings. TREMprime WB is asbestos free, easy to use, and is low in volatile organic compounds to meet the requirements of the National Architectural Coatings regulation.

### BASIC USES

TREMprime WB promotes adhesion between new and weathered surfaces and Tremco Roofing Systems and coatings.

### PACKAGING

TREMprime WB is available in 1 gallon (3.78L), 5 gallon (19L) containers and 53 gallon (200L) plastic lined drums.

### GRADE

Brush, Roll, Spray

### STORAGE LIFE

One year.

### APPLICATION

**Recommended Spray Equipment:** Minimum 11:1 ratio pump with 0.015" to 0.021" spray tip.

**Application:** Remove all loose dust, dirt, rotted felt, and foreign matter. Surface must be clean and dry. When spraying Tremprime WB take necessary precautions to prevent overspray.

### COVERAGE

Coverage will vary depending upon actual surface and application conditions. Approximately 200-400 sq ft/gal (4.9-9.8 m<sup>2</sup>/L).

### CLEAN UP

Promptly clean tools and equipment with soap and water. Dried primer can be cleaned with mineral spirits.

### LIMITATIONS

- Not intended to be used as a final coating.
- Do not apply when rain appears imminent.
- Do not apply below 45°F (7°C).
- Do not freeze container.
- Store indoors in a heated area.
- Surfaces primed with Tremprime WB must be reprimed if open for more than 24 hours.

# TREMprime WB

## PHYSICAL PROPERTIES

| PROPERTY                               | TYPICAL VALUE                        | TEST METHOD      |
|--|--------------------------------------|------------------|
| Asbestos content                       | None                                 | EPA 600/R-93/116 |
| Viscosity @ 77°F (25°C) (Stormer-Kreb) | 50 KU                                | ASTM D 562       |
| Density @ 77°F (25°C)                  | 8.5 lb/gal (1018 kg/m <sup>3</sup> ) | ASTM D 1475      |
| Nonvolatile content                    | 46%                                  | ASTM D 2823      |
| Flash Point                            | Not applicable                       | ASTM D 3278      |
| pH                                     | 9.1                                  | ASTM E 70        |
| VOC                                    | 2 g/l                                | ASTM D 3960      |
| Color                                  | Brown/black                          |                  |

## MAINTENANCE

Your local Tremco Roofing sales representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

## PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

## TECHNICAL SUPPORT

Your local Tremco Roofing sales representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



[www.tremcoroofing.com](http://www.tremcoroofing.com)  
3735 Green Road  
Beachwood, Ohio 44122  
1.800.852.6013

220 Wicksteed Avenue  
Toronto, Ontario, M4H 1G7  
1.800.668.9879

Tremco Roofing and Building  
Maintenance is part of Tremco  
Construction Products Group.

Tremco is a US Registered trademark of Tremco CPG Inc.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.