# TremLock Board and Batten

## **FEATURES**

#### **BENEFITS**

- Architectural design
- Nostalgic look

**DESCRIPTION** 

The TremLock Board & Batten concealed fastener siding system offers the time-honored look of wood siding without the hassle of ongoing maintenance.

**BASIC USES** 

From residential to light commercial, building owners and designers appreciate the unique aesthetic appearance, carefree maintenance, and increased resistance to fire, rot, and insects over its wooden predecessors.

**SYSTEM DESIGN** 

Standard 24 Ga Galvalume®

**FINISH / COLOR** 

The standard paint system for the Board & Batten panel is Kynar 500® (PVDF), the industry's best coating for long-term protection against panel chalk and fade.


**APPLICATION** 

Wall Panel

**PROFILES** 



NOSTALGIA BOARD and BATTEN SEAM



# PHYSICAL PROPERTIES

## **TESTING\***

Uplift: ASTM E1592 (Pending)

Wind: ASTM E283, ASTM E331 (Pending)

\*Testing and Approvals are product specific. Please inquire for details

**MAINTENANCE** 

Your local Tremco Roofing Sales Representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

**PRECAUTIONS** 

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

**TECH SUPPORT** 

Your local Tremco Roofing Sales Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



3735 Green Road Beachwood, Ohio 44122

220 Wicksteed Avenue Toronto, Ontario, M4H 1G7

www.tremcoroofing.com

1.800.852.6013

Tremco Roofing and Building Maintenance is part of Tremco Construction Products Group. Tremco is a US Registered trademark of Tremco CPG Inc.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Termoc DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY; NA LL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.