

Tremco Infinity Coping	Inside Face	Wall Width	Outside Face	Material	Perimeter FM Rating	Corner FM Rating	ES-1 Rating
TremLock Infinity Coping	4	10	6	.050, .063	1-240	1-150	403
TremLock Infinity Coping	4	12	6	.050, .063	1-225	1-150	393
TremLock Infinity Coping	4	16	6	.050, .063	1-150	1-105	272
TremLock Infinity Coping	4	16	12	.050, .063	1-120	1-75	202
TremLock Infinity Coping	4	24	6	.050, .063	1-105	1-60	186
TremLock Infinity Coping	4	24	12	.050, .063	1-105	1-75	191
TremLock Infinity Coping	4	32	6	.050, .063	1-90	1-60	152
TremLock Infinity Coping	4	10	6	24ga, 22ga, .040	1-210	1-135	363
TremLock Infinity Coping	4	12	6	24ga, 22ga, .040	1-150	1-90	263
TremLock Infinity Coping	4	16	6	24ga, 22ga, .040	1-135	1-90	231
TremLock Infinity Coping	4	16	12	24ga, 22ga, .040	1-75	NA	147
TremLock Infinity Coping	4	24	6	24ga, 22ga, .040	1-75	NA	131

Tremco Infinity Flush Coping	Inside Face	Wall Width	Outside Face	Material	Perimeter FM Rating	Corner FM Rating	ES-1 Rating
TremLock Infinity Flush Coping	4	10	6	.050, .063	1-300	1-195	513
TremLock Infinity Flush Coping	4	12	6	.050, .063	1-240	1-150	403
TremLock Infinity Flush Coping	4	16	6	.050, .063	1-150	1-90	261
TremLock Infinity Flush Coping	4	16	12	.050, .063	1-150	1-90	261
TremLock Infinity Flush Coping	4	24	6	.050, .063	1-135	1-90	236
TremLock Infinity Flush Coping	4	24	12	.050, .063	1-105	1-75	191
TremLock Infinity Flush Coping	4	32	6	.050, .063	1-90	1-60	171
TremLock Infinity Flush Coping	4	10	6	24ga, 22ga, .040	1-225	1-150	383
TremLock Infinity Flush Coping	4	12	6	24ga, 22ga, .040	1-195	1-135	343
TremLock Infinity Flush Coping	4	16	6	24ga, 22ga, .040	1-135	1-90	232
TremLock Infinity Flush Coping	4	16	12	24ga, 22ga, .040	1-135	1-90	232
TremLock Infinity Flush Coping	4	24	6	24ga, 22ga, .040	1-120	1-75	211
TremLock Infinity Flush Coping	4	24	12	24ga, 22ga, .040	1-90	1-60	171

Tremco Infintiy Gold Coping	Inside Face	Wall Width	Outside Face	Material	Perimeter FM Rating	Corner FM Rating	ES-1 Rating
TremLock Infinity Gold Coping	4	10	6	.050, .063	1-300	1-195	513
TremLock Infinity Gold Coping	4	12	6	.050, .063	1-240	1-150	403
TremLock Infinity Gold Coping	4	16	6	.050, .063	1-150	1-90	261
TremLock Infinity Gold Coping	4	16	12	.050, .063	1-150	1-90	261
TremLock Infinity Gold Coping	4	24	6	.050, .063	1-135	1-90	236
TremLock Infinity Gold Coping	4	24	12	.050, .063	1-105	1-75	191
TremLock Infinity Gold Coping	4	32	6	.050, .063	1-90	1-60	171
TremLock Infinity Gold Coping	4	10	6	24ga, 22ga, .040	1-225	1-150	383
TremLock Infinity Gold Coping	4	12	6	24ga, 22ga, .040	1-195	1-135	343
TremLock Infinity Gold Coping	4	16	6	24ga, 22ga, .040	1-135	1-90	232
TremLock Infinity Gold Coping	4	16	12	24ga, 22ga, .040	1-135	1-90	232
TremLock Infinity Gold Coping	4	24	6	24ga, 22ga, .040	1-120	1-75	211
TremLock Infinity Gold Coping	4	24	12	24ga, 22ga, .040	1-90	1-60	171

Tremco Infinity Cleat Coping	Inside Face	Wall Width	Outside Face	Material	Perimeter FM Rating	Corner FM Rating	ES-1 Rating
TremLock Infinity Cleat Coping	4	16	6	.050, .063	1-240	1-165	422
TremLock Infinity Cleat Coping	4	16	12	.050, .063	1-225	1-90	402
TremLock Infinity Cleat Coping	4	24	6	.050, .063	1-135	1-150	226
TremLock Infinity Cleat Coping	4	24	12	.050, .063	1-135	1-90	241
TremLock Infinity Cleat Coping	4	32	6	.050, .063	1-105	1-60	182
TremLock Infinity Cleat Coping	4	16	6	24ga, 22ga, .040	1-180	1-120	312
TremLock Infinity Cleat Coping	4	16	12	24ga, 22ga, .040	1-150	1-90	272
TremLock Infinity Cleat Coping	4	24	6	24ga, 22ga, .040	1-90	1-60	166
TremLock Infinity Cleat Coping	4	24	12	24ga, 22ga, .040	1-90	1-60	171

Tremco Traverse Coping	Inside Face	Wall Width	Outside Face	Material	Perimeter FM Rating	Corner FM Rating	ES-1 Rating
TremLock Traverse Coping	4	16	6	.050, .063	1-120	1-75	221
TremLock Traverse Coping	4	24	10	.050, .063	1-90	1-60	161
TremLock Traverse Coping	4	16	6	24ga, 22ga, .040	1-120	1-75	221
TremLock Traverse Coping	4	24	10	24ga, 22ga, .040	1-90	NA	151

Tremco 215 Fascia & Extruded Drip Edge	Face Height	Perimeter FM Rating	Corner FM Rating	FM	ES-1 Rating	Wind Warranty	Duration	Materials	Cleat Type	Installation Method	Custom Sizes
Tremlock 215 Fascia Single Ply	4" + 5-1/2"	I-270	I-225		275	215 mph	Lifetime	24ga, 22ga + .040	Extruded Aluminum	Snap-On	No
Tremlock 215 Fascia Single Ply	7" + 8-1/2"	I-180	I-135		155	215 mph	Lifetime	24ga, 22ga + .040	Extruded Aluminum	Snap-On	No
Tremlock 215 Fascia BUR/MB	5-1/2"	I-270	I-225		275	215 mph	Lifetime	24ga, 22ga + .040	Extruded Aluminum	Snap-On	No
Tremlock 215 Fascia BUR/MB	7" + 8-1/2"	I-150	I-120		155	215 mph	Lifetime	24ga, 22ga + .040	Extruded Aluminum	Snap-On	No
Tremlock 215 EXT Fascia Single Ply	8-1/2" to 13"	I-180	I-135		176	215 mph	Lifetime	.050, .063	Extruded Aluminum	Snap-On	Yes
Tremlock 215 EXT Fascia BUR/MB	8-1/2" to 13"	I-180	I-135		176	215 mph	Lifetime	.050, .063	Extruded Aluminum	Snap-On	Yes
Tremlock 215 Canted Fascia	5-1/2", 7 1/2"	I-135	I-105		139	215 mph	Lifetime	.050, .063	Extruded Aluminum	Snap-On	Yes
Tremlock 215 EXT Canted Fascia	9", 10-1/2", 12", 13-1/2"	I-135	I-105		139	215 mph	Lifetime	.050, .063	Extruded Aluminum	Snap-On	Yes
Tremlock 215 HD Fascia Single Ply	4", 5-1/2", 7"	I-375	I-300		365	215 mph	Lifetime	.050, .063	Extruded Aluminum	Snap-On	No
Tremlock 215 HD Fascia BUR/MB	5-1/2" + 7"	I-375	I-300		365	215 mph	Lifetime	.050, .063	Extruded Aluminum	Snap-On	No
Tremlock 215 Drip Edge	4-1/2 + 6"	I-585	I-465		577	215 mph	Lifetime	24ga, 22ga + .040	Extruded Aluminum	Snap-On	No

Tremco Eco Edge Fascia	Face Height	Perimeter FM Rating	Corner FM Rating	FM	ES-1 Rating	Wind Warranty	Duration	Materials	Cleat Type	Installation Method	Custom Sizes
TremLock Eco Edge Single Ply	4" + 5"	I-405	I-315		396	120 mph	20 Year	24ga, 22ga + .040	Formed 20ga Steel	Snap-On	Yes
TremLock Eco Edge Single Ply	6-1/2 + 8"	I-150	I-120		155	120 mph	20 Year	24ga, 22ga + .040	Formed 20ga Steel	Snap-On	Yes
TremLock Eco Edge MB	5"	I-420	I-345		419	120 mph	5 Year	24ga, 22ga + .040	Formed 20ga Steel	Snap-On	Yes
TremLock Eco Edge MB	6-1/2 + 8"	I-180	I-135		179	120 mph	5 Year	24ga, 22ga + .040	Formed 20ga Steel	Snap-On	Yes
TremLock Eco Edge Extended Fascia Single Ply	9-1/2", 11", 12-1/2"	I-150	I-120		146	120 mph	5 Year	.050, .063	Formed 20ga Steel	Snap-On	Yes
TremLock Eco Edge Extended Fascia BUR/MB	9-1/2", 11", 12-1/2"	I-150	I-120		146	120 mph	5 Year	.050, .063	Formed 20ga Steel	Snap-On	Yes

Tremco 200 & 300 Fascia	Face Height	Perimeter FM Rating	Corner FM Rating	ES-1 Rating	Wind Warranty	Duration	Materials	Cleat Type	Installation Method	Custom Sizes
TremLock 200S Fascia	5-1/4" to 8-1/4"	I-195	I-150	196	120 mph	20 Year	24ga, 22ga + .040	Formed 24ga Steel	Snap-On	Yes
TremLock 200S Fascia	5-1/4" to 8-1/4"	I-210	I-165	216	120 mph	20 Year	.050, .063	Formed 24ga Steel	Snap-On	Yes
TremLock 200S Fascia	9-3/4" to 12-3/4"	I-120	I-90	116	120 mph	20 Year	.050, .063	Formed 24ga Steel	Snap-On	Yes
TremLock 300S Fascia	5-1/4" to 8-1/4"	I-195	I-150	196	120 mph	20 Year	24ga, 22ga + .040	Formed 24ga Steel	Snap-On	Yes
TremLock 300S Fascia	5-1/4" to 8-1/4"	I-210	I-165	216	120 mph	20 Year	.050, .063	Formed 24ga Steel	Snap-On	Yes
TremLock 300S Fascia	9-3/4" to 12-3/4"	I-120	I-90	116	120 mph	20 Year	.050, .063	Formed 24ga Steel	Snap-On	Yes

Tremco Drip Edge & Gravel Stop	Face Height	Perimeter FM Rating	Corner FM Rating	ES-1 Rating	Wind Warranty	Duration	Materials	Cleat Type	Installation Method	Custom Sizes
TremLock Eco-Slot Drip Edge	6" or Less	I-285	I-225	276	90 mph	10 Year	22ga, 24ga, .040, .050 .063	Formed 22ga Steel	Fastened/ Stripped In	Yes
TremLock Eco Drip Edge S	6" or Less	I-285	I-225	282	90 mph	10 Year	22ga, 24ga, .040, .050 .063	Formed 22ga Steel	Fastened/ Stripped In	Yes
TremLock Eco Drip Edge S	>6" to 10"	I-180	I-135	177	90 mph	10 Year	22ga, 24ga, .040, .050 .063	Formed 22ga Steel	Fastened/ Stripped In	Yes
TremLock Eco Gravel Stop	6" or Less	I-210	I-165	216	90 mph	10 Year	22ga, 24ga, .040, .050 .063	Formed 22ga Steel	Fastened/ Stripped In	Yes
TremLock Eco Gravel Stop	>6" to 10"	I-255	I-210	258	90 mph	10 Year	22ga, 24ga, .040, .050 .063	Formed 22ga Steel	Fastened/ Stripped In	Yes