

SAFETY DATA SHEET

1. Identification

Material name: WALLTITE-WHITE 5USGL Material: 086700A512

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Incorporated 3735 Green Road BEACHWOOD OH 44122 US

Contact person: Telephone: Emergency telephone number: EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards	
Acute toxicity (Inhalation - dust and mist)	Category 4
Carcinogenicity	Category 1A
Unknown toxicity - Health	
Acute toxicity, oral	33.9 %
Acute toxicity, dermal	38.66 %
Acute toxicity, inhalation, vapor	99.95 %
Acute toxicity, inhalation, dust or mist	73.05 %
Environmental Hazards	
Acute hazards to the aquatic environment	Category 3
Unknown toxicity - Environment	
Acute hazards to the aquatic environment	64.45 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:





	Signal Word:	Danger
	Hazard Statement:	Harmful if inhaled. May cause cancer. Harmful to aquatic life.
	Precautionary Statement: Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a
		well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
	Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
	Storage:	Store locked up.
	Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
-	nazards which do not n GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Other result

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Titanium dioxide	13463-67-7	3 - 7%
Propylene glycol	57-55-6	1 - 5%
Zinc oxide	1314-13-2	1 - 5%
Cellulose	9004-34-6	1 - 5%
Clay	1332-58-7	0.1 - 1%
Magnesite	546-93-0	0.1 - 1%
Heavy paraffinic distillate	64741-88-4	0.1 - 1%
Aluminum oxide	1344-28-1	0.1 - 1%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1%
Amorphous silica	7631-86-9	0.1 - 1%

All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor//if you feel unwell. Rinse mouth.
Inhalation:	Move to fresh air.
Skin Contact:	Wash skin thoroughly with soap and water. Get medical attention if symptoms occur.



Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.	
Most important symptoms/effect	s, acute and delayed	
Symptoms:	May cause skin and eye irritation.	
Indication of immediate medical a	ttention and special treatment needed	
Treatment:	Symptoms may be delayed.	
5. Fire-fighting measures		
General Fire Hazards:	No unusual fire or explosion hazards noted.	
Suitable (and unsuitable) ex	xtinguishing media	
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.	
Special protective equipment an	d precautions for firefighters	
Special fire fighting procedures:	No data available.	
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.	
6. Accidental release measures	S	
Personal precautions, protective equipment and emergency procedures:	No data available.	
Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.	
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.	
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.	



7. Handling and storage

Precautions for safe handling:	Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities:	Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	STEL	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Zinc oxide - Fume.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Cellulose	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Cellulose - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Cellulose - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Clay - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Clay - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air



			Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Heavy paraffinic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Heavy paraffinic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Heavy paraffinic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Crystalline Silica (Quartz)/ Silica Sand - Total dust.	TWA	0.3 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Amorphous silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)



Chemical name	type	Exposure Lin	nit Values	Source
Calcium carbonate - Total dust.	STEL		20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Propylene glycol - Aerosol.	TWAEV		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Propylene glycol - Vapor and aerosol, inhalable fraction.	TWAEV	50 ppm	155 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zinc oxide - Respirable.	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Zinc oxide - Respirable fraction.	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zinc oxide - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry o Labor - Regulation Respecting the Quality of the Work Environment) (* 2008)
Zinc oxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry o Labor - Regulation Respecting the Quality of the Work Environment) (* 2008)
Zinc oxide - Fume.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry o Labor - Regulation Respecting the Quality of the Work Environment) (2008)
Cellulose - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupationa Health and Safety Regulation 296/9 as amended) (07 2007)
Cellulose - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupationa Health and Safety Regulation 296/9 as amended) (07 2007)
Cellulose	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cellulose - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry or Labor - Regulation Respecting the Quality of the Work Environment) (* 2008)
Heavy paraffinic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupationa Health and Safety Regulation 296/9 as amended) (07 2007)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupationa Health and Safety Regulation 296/9 as amended) (07 2007)
Heavy paraffinic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Heavy paraffinic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry or Labor - Regulation Respecting the Quality of the Work Environment) (7 2008)



			Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWAEV	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	White
Odor:	Mild
Odor threshold:	No data available.
pH:	9 - 10
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	100 °C 212 °F
Flash Point:	No data available.



Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosi	ve limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.33
Solubility(ies)	
Solubility in water:	Soluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of Hazardous Reactions:	No data available.
Conditions to Avoid:	Avoid heat or contamination.
Incompatible Materials:	Strong acids. Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of ex Ingestion:	posure May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin.
Eye contact:	Eye contact is possible and should be avoided.



Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product:	No data available.
Dermal Product:	ATEmix: 3,928.84 mg/kg
Inhalation Product:	ATEmix: 3.06 mg/l
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.
Serious Eye Damage/Eye Irritation Product:	on No data available.
Specified substance(s): Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Titanium dioxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Propylene glycol	(Human): Irritating
Zinc oxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Magnesite	In vitro (Reconstituted Corneal Epithelium model, 10 min): Not irritating
Heavy paraffinic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Aluminum oxide	in vivo (Rabbit, 24 hrs): Not irritating
Amorphous silica	in vivo (Rabbit, 24 hrs): Not irritating
Respiratory or Skin Sensitization Product:	n No data available.

Carcinogenicity Product:

No data available.



IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dio	xide Overall evaluat	ion: Possibly carcinogenic to humans.
Heavy paraff distillate		ion: Not classifiable as to carcinogenicity to humans. Overall cinogenic to humans.
Crystalline S (Quartz)/ Sili Sand		ion: Carcinogenic to humans.
US. National Toxicology	Program (NTP) Report	on Carcinogens:

Heavy paraffinic Known To Be Human Carcinogen. distillate Crystalline Silica Known To Be Human Carcinogen. (Quartz)/ Silica Sand

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified

Germ Cell Mutagenicity

In vitro Product:	No data available.	
In vivo Product:	No data available.	
Reproductive toxicity Product:	No data available.	
Specific Target Organ Toxicit Product:	y - Single Exposure No data available.	
Specific Target Organ Toxicity - Repeated Exposure Product: No data available.		
Aspiration Hazard Product:	No data available.	
Other effects:	No data available.	

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:



Fish Product:	No data available.	
Specified substance(s): Calcium carbonate	LC 50 (Western mosquitofish (Gambusia affinis), 96 h): > 56,000 mg. Mortality	/I
Titanium dioxide	LC 50 (Mummichog (Fundulus heteroclitus), 96 h): > 1,000 mg/l Mort	ality
Propylene glycol	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 55,770 mg/l I	Mortality
Zinc oxide	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2,246 mg/l M	ortality
Aquatic Invertebrates Product:	No data available.	
Specified substance(s): Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication	
Propylene glycol	EC 50 (Water flea (Daphnia magna), 48 h): > 10,000 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): > 10,000 mg/l Intoxication LC 50 (Brine shrimp (Artemia salina), 24 h): > 10,000 mg/l Mortality	
Zinc oxide	LC 50 (Water flea (Daphnia magna), 48 h): 24.6 mg/l Mortality	
Chronic hazards to the aquati	c environment:	
Fish Product:	No data available.	
Specified substance(s): Titanium dioxide	LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimen result	tal
Propylene glycol	NOAEL (Pimephales promelas, 7 d): 11,530 mg/l experimental result	Ċ
Zinc oxide	NOAEL (Oncorhynchus mykiss, 30 d): 974 μ g/l interpreted	
Heavy paraffinic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR	
Aluminum oxide	NOAEL (Pimephales promelas, 28 d): 4.7 mg/l experimental result	
Aquatic Invertebrates Product:	No data available.	
Toxicity to Aquatic Plants Product:	No data available.	
Persistence and Degradability		
Biodegradation Product:	No data available.	
BOD/COD Ratio Product:	No data available.	12/16
00000050/00		12,10



Bioaccumulative Potential Bioconcentration Factor (B	CF)		
Product:	No data available.		
Partition Coefficient n-octar Product:	nol / water (log Kow) No data available.		
Specified substance(s): Propylene glycol	Log Kow: -0.92		
Mobility in Soil:	No data available.		
Other Adverse Effects:	Harmful to aquatic organisms.		
13. Disposal considerations			
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.		
Contaminated Packaging:	No data available.		
14. Transport information			
TDG:			
Not Regulated			
CFR / DOT:			

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) None present or none present in regulated quantities.



CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Ammonium hydroxide	1000 lbs.
Ammonia	100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

	<u>Reportable</u>	
Chemical Identity	quantity	Threshold Planning Quantity
Ammonia	100 lbs.	500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Zinc oxide	
Ammonium hydroxide	1000 lbs.
Ammonia	100 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Ammonia	500lbs
Calcium carbonate	500 lbs
Titanium dioxide	500 lbs
Propylene glycol	500 lbs
Zinc oxide	500 lbs
Cellulose	500 lbs
Clay	500 lbs
Magnesite	500 lbs
Heavy paraffinic distillate	500 lbs
Aluminum oxide	500 lbs
Crystalline Silica (Quartz)/	500 lbs
Silica Sand	
Amorphous silica	500 lbs

SARA 313 (TRI Reporting)

Chemical Identity Zinc oxide

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Chemical Identity	Reportable quantity
Ammonia	10000 lbs
Ammonia	20000 lbs

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.



US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium carbonate Titanium dioxide Propylene glycol Zinc oxide Cellulose

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium carbonate Titanium dioxide Zinc oxide Cellulose Crystalline Silica (Quartz)/ Silica Sand Ammonia

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity Calcium carbonate Titanium dioxide Propylene glycol Zinc oxide Cellulose

US. Rhode Island RTK

Chemical Identity

Zinc oxide

Other Regulations:

Regulatory VOC (less water	67 g/l
and exempt solvent):	
VOC Method 310:	2.70 %

Inventory Status: Australia AICS: One or more components in this product are not listed on or exempt from the Inventory. All components in this product are listed on or Canada DSL Inventory List: exempt from the Inventory. EINECS, ELINCS or NLP: One or more components in this product are not listed on or exempt from the Inventory. Japan (ENCS) List: One or more components in this product are not listed on or exempt from the Inventory. China Inv. Existing Chemical Substances: One or more components in this product are not listed on or exempt from the Inventory. Korea Existing Chemicals Inv. (KECI): One or more components in this product are not listed on or exempt from the Inventory.



Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	08/14/2015
Version #:	1.0
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.